

## Wi-Fi CERTIFIED™ Certificate



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

## Certification ID: WFA130744

## **Product Info**

Date of Certification	June 7, 2024
Company	APSI
Product Name	SKYPHONE
Product Model Variant	SKYPHONE
Model Number	SKYPHONE
Category	Phones
Sub-category	Smartphone

## **Summary of Certifications**

CLASSIFICATION	CERTIFICATION
Connectivity	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n
Optimization	WMM® Wi-Fi Agile Multiband™
Security	Protected Management Frames WPA2 <sup>™</sup> -Enterprise 2018-04 WPA2 <sup>™</sup> -Personal 2021-01 WPA3 <sup>™</sup> -Enterprise 2022-12 WPA3 <sup>™</sup> -Personal 2022-06



## Wi-Fi CERTIFIED™ Certificate

**Certification ID: WFA130744** 



Role: Station	Pa	Page 2 of 3	
Wi-Fi Components			
Wi-Fi Component Operating System	RF Architecture		
Android	Bands Supported	Transmit (Tx)	Receive (Rx)
Wi-Fi Component Firmware			
2.0.0.1111.1	2.4 GHz	1	1
	5 GHz	1	1
Certifications			
2.4 GHz Spectrum Capabilities	WPA2™-Enterpris	e 2018-04 (cont	inued)
20 MHz Channel Width in 2.4 GHz	PEAPv1		
40 MHz Channel Width in 2.4 GHz			
	WPA2™-Personal	2021-01	
5 GHz Spectrum Capabilities	WPA3™-Enterpris	0 2022 12	
20 MHz Channel Width in 5 GHz	WPA3 ····-Enterpris	e 2022-12	
40 MHz Channel Width in 5 GHz	EAP methods		
80 MHz Channel Width in 5 GHz	EAP AKA		
160 MHz Channel Width in 5 GHz	EAP AKA Prime EAP SIM		
	EAP TLS		
Protected Management Frames	EAP TTLS		
WMM®	PEAPv0		
	PEAPv1 Server Certificate Valida	tion	
WPA2™-Enterprise 2018-04			
EAP methods	WPA3™-Personal	2022-06	
EAP AKA			
EAP AKA Prime	Wi-Fi Agile Multib	and™	
EAP SIM EAP TLS	Wi-Fi CERTIFIED	6R	
EAP TTLS			
PEAPv0	A-MPDU with A-MSDU		



# Wi-Fi CERTIFIED™ Certificate

**Certification ID: WFA130744** 



## **Role: Station**

## Page 3 of 3

### Wi-Fi CERTIFIED 6® (continued)

**BSRP** Trigger frame Compressed Block Ack Rx (buffer size 256) Compressed Block Ack Tx (buffer size 256) DL MU-MIMO DL MU PPDU multi-tone HE NDP LDPC Tx LDPC Rx Individual Target Wake Time MCS 10-11 Rx MCS 10-11 Tx MCS 8-9 Rx MCS 8-9 Tx MU EDCA Parameter Set element **MU-BAR Trigger frame** MU-RTS Trigger frame Operating mode control field Operating mode subfield in A-Control field SU beamformee UL OFDMA UL TB PPDU multi-tone

#### Wi-Fi CERTIFIED™ a

#### Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU DL MU-MIMO LDPC Rx MCS 8-9 Rx Short Guard Interval STBC LDPC Tx SU beamformee

#### Wi-Fi CERTIFIED™ b

### <u>Wi-Fi CER</u>TIFIED™ g

#### Wi-Fi CERTIFIED™ n

A-MPDU Tx
HT Duplicate Mode
OBSS on Extension Channel
Short Guard Interval
STBC