



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA129256

Product Info

Date of Certification April 26, 2024

Company Harman International Industries, Inc.

Product Name MGU22 H

Product Model Variant MGU22 H

Model Number MGU22H

Category Other

Sub-category In-vehicle Network

Summary of Certifications

CLASSIFICATION CERTIFICATION

Connectivity 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities

Wi-Fi CERTIFIED 6®
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n

Optimization WMM®

Wi-Fi Agile Multiband™

Security Protected Management Frames

WPA2[™]-Personal 2021-01 WPA3[™]-Personal 2022-06



Certification ID: WFA129256



Role: Access Point Page 2 of 5

Wi-Fi Components

Wi-Fi Component Operating System

Linux

Wi-Fi Component Firmware

PCIE9098--w9098o-V1, RF878X, FP68_LINUX, 17.68.1.p149.37-MXM5X17405.p33-GPL-(FP68)

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz 40 MHz Channel Width in 5 GHz 80 MHz Channel Width in 5 GHz

Wi-Fi CERTIFIED 6® (continued)

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx MCS 10-11 Tx

OM subfield in A-Control field

SU beamformer

Protected Management Frames

WMM®

Max Throughput

WPA2™-Personal 2021-01

WPA3™-Personal 2022-06

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU LDPC Rx

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU

LDPC Rx

LDPC Tx

MCS 8-9 Rx

Short Guard Interval

SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n





Certification ID: WFA129256

Role: Access Point Wi-Fi CERTIFIED™ n (continued) HT Duplicate Mode OBSS on Extension Channel Short Guard Interval A-MPDU Tx



Certification ID: WFA129256



Role: Station Page 4 of 5

Wi-Fi Components

Wi-Fi Component Operating System

Linux

Wi-Fi Component Firmware

PCIE9098--w9098o-V1, RF878X, FP68_LINUX, 17.68.1.p149.37-MXM5X17405.p33-GPL-(FP68)

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz

Wi-Fi Agile Multiband™ (continued)

Cellular Data capable

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz

40 MHz Channel Width in 5 GHz

80 MHz Channel Width in 5 GHz

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU

Beamforming sounding

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

DL Mu PPDU multi-tone

HE NDP

LDPC Tx

LDPC Rx

MCS 10-11 Rx

MCS 10-11 Tx

MCS 8-9 Rx

MCS 8-9 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

MU-RTS Trigger frame

OM subfield in A-Control field

Operating Mode indication

SU beamformee

Protected Management Frames

WMM®

Max Throughput

WPA2™-Personal 2021-01

WPA3™-Personal 2022-06

Wi-Fi Agile Multiband™

ANQP

BTM Query





Certification ID: WFA129256

Role: Station	Page 5 of 5
Wi-Fi CERTIFIED 6® (continued)	
SU-MIMO	
UL OFDMA	
UL TB PPDU multi-tone	
Wi-Fi CERTIFIED™ a	
Wi-Fi CERTIFIED™ ac	
A-MPDU with A-MSDU	
DL MU-MIMO	
LDPC Rx	
MCS 8-9 Rx	
Short Guard Interval	
LDPC Tx	
SU beamformee	
Wi-Fi CERTIFIED™ b	
Wi-Fi CERTIFIED™ g	
Wi-Fi CERTIFIED™ n	
A-MPDU Tx	
OBSS on Extension Channel	
Short Guard Interval	