



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA123248

Product Info

Date of Certification May 2, 2024

Company NXP Semiconductors

Product Name 9098

Product Model Variant 9098-R10.9_G

Model Number 9098

Category Other

Sub-category Embedded Module

Summary of Certifications

CLASSIFICATION CERTIFICATION

Access Wi-Fi Protected Setup™

Connectivity 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities

Wi-Fi CERTIFIED 6®
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ ac
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n

Wi-Fi Direct®

Optimization WMM®

Wi-Fi Agile Multiband™

Security Protected Management Frames

WPA2[™]-Personal 2021-01 WPA3[™]-Personal 2022-06

Spectrum & Regulatory

Features

Spectrum & Regulatory



Certification ID: WFA123248



Role: Access Point Page 2 of 5

Wi-Fi Components

Wi-Fi Component Operating System

Linux

Wi-Fi Component Firmware

p149.42

RF Architecture

Bands Supported Transmit (Tx) Receive (Rx)

2.4 GHz 2 2

5 GHz 2 2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz 40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz

40 MHz Channel Width in 5 GHz

80 MHz Channel Width in 5 GHz

WPA3™-Personal 2022-06

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx SU beamformer

Protected Management Frames

Spectrum & Regulatory

802.11d

802.11h

WMM®

Max Throughput

WPA2™-Personal 2021-01

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU

Extended 5 GHz Channel Support

LDPC Rx

LDPC Tx

MCS 8-9 Rx

RTS with BW Signaling

Short Guard Interval

SU beamformer





Certification ID: WFA123248

Role: Access Point	Page 3 of 5
Wi-Fi CERTIFIED™ b	
Wi-Fi CERTIFIED™ g	
Wi-Fi CERTIFIED™ n	
HT Duplicate Mode OBSS on Extension Channel Short Guard Interval A-MPDU Tx	
Wi-Fi Protected Setup™	
PIN Pushbutton	



Certification ID: WFA123248



Role: Station Page 4 of 5

Wi-Fi Components

Wi-Fi Component Operating System

Linux

Wi-Fi Component Firmware

p149.42

RF Architecture

Bands Supported Transmit (Tx) Receive (Rx)

2.4 GHz 2 2

5 GHz 2 2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz 40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz 40 MHz Channel Width in 5 GHz

80 MHz Channel Width in 5 GHz

oo mile onamor waar iir o or ie

Protected Management Frames

Spectrum & Regulatory

802.11d 802.11h

WMM®

Max Throughput

WPA2™-Personal 2021-01

WPA3™-Personal 2022-06

Wi-Fi Agile Multiband™

ANQP

BTM Query

Cellular Data capable

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU

Beamforming sounding

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

DL Mu PPDU multi-tone

HE NDP

LDPC Tx

LDPC Rx

MCS 10-11 Rx

MCS 10-11 Tx

MCS 8-9 Rx

MCS 8-9 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame





Certification ID: WFA123248

Role: Station Page 5 of 5

Wi-Fi CERTIFIED 6® (continued)

MU-RTS Trigger frame

Operating Mode indication

SU beamformee

SU-MIMO

UL OFDMA

UL TB PPDU multi-tone

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

Extended 5 GHz Channel Support

RTS with BW Signaling

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

MCS 8-9 Rx

Short Guard Interval

LDPC Tx

SU beamformee

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx

OBSS on Extension Channel

Power Management

Short Guard Interval

Wi-Fi Direct®

Wi-Fi Protected Setup™

PIN

Pushbutton