



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

# **Certification ID: WFA131572**

## **Product Info**

**Date of Certification** June 24, 2024

Company Intel

Product Name Intel® Wi-Fi 7 BE201

Product Model Variant Win11 - 23.70

Model Number BE201

Category Computers & Accessories

**Sub-category** External Adapter

# **Summary of Certifications**

CI	ASSIFICATION	CERTIFICATION

**Connectivity** 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities 6 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Release 2

Wi-Fi CERTIFIED 7™
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n

Wi-Fi Enhanced Open™ 2023-12

**Optimization** WMM®

WMM®-Power Save Wi-Fi Agile Multiband™ Wi-Fi QoS Management™

**Security** Protected Management Frames

WPA2<sup>™</sup>-Enterprise 2018-04 WPA2<sup>™</sup>-Personal 2021-01 WPA3<sup>™</sup>-Enterprise 2022-12 WPA3<sup>™</sup>-Personal 2023-12





**Certification ID: WFA131572** 

0	f Coultifications	/ <del>4!   \</del>
Summary	of Certifications	(continuea)

Page 2 of 5

**CLASSIFICATION** 

**CERTIFICATION** 

Spectrum & Regulatory

Spectrum & Regulatory

**Features** 



**Certification ID: WFA131572** 



Role: Station		Page 3 of 5		
Wi-Fi Components				
Wi-Fi Component Operating System	RF Architecture			
Windows 11	Bands Supported	Transmit (Tx)	Receive (Rx)	
Wi-Fi Component Firmware	2.4 GHz	2	2	
23.70	5 GHz	2	2	
	6 GHz	2	2	
Certifications				
2.4 GHz Spectrum Capabilities	Spectrum & Reg	Spectrum & Regulatory (continued)		
20 MHz Channel Width in 2.4 GHz	802.11d			
40 MHz Channel Width in 2.4 GHz	802.11h			
5 GHz Spectrum Capabilities	WMM®			
20 MHz Channel Width in 5 GHz	WMM®-Power Sa	WMM®-Power Save		
40 MHz Channel Width in 5 GHz 80 MHz Channel Width in 5 GHz	Legacy Power Save			
160 MHz Channel Width in 5 GHz	Unschedule auto PS			
6 GHz Spectrum Capabilities	WPA2™-Enterpr	ise 2018-04		
20 MHz Channel Width in 6 GHz	EAP methods			
40 MHz Channel Width in 6 GHz	EAP TLS			
80 MHz Channel Width in 6 GHz  160 MHz Channel Width in 6 GHz	EAP TTLS PEAPv0			
320 MHz channel width in 6 GHz	FLAFVU			
Protected Management Frames	WPA2™-Persona	al 2021-01		
	WPA3™-Enterpr	ise 2022-12		



Certification ID: WFA131572 CER



Role: Station Page 4 of 5

#### WPA3™-Enterprise 2022-12 (continued)

EAP methods

**EAP TLS** 

**EAP TTLS** 

PEAPv0

192-bit security

192-bit security RSA 3K with the

TLS\_ECDHE\_RSA\_WITH\_AES\_256\_GCM\_SHA384

cipher suite

Fast Transition OTA on WPA3-Enterprise

Server Certificate Validation

## WPA3™-Personal 2023-12

AKM 24

**Beacon Protection** 

## Wi-Fi Agile Multiband™

Beacon Report Measurement Active Mode

Beacon Report Measurement Passive Mode

Fast Transition OTA on WPA2-Enterprise

#### Wi-Fi CERTIFIED 6® Release 2

A-MPDU with A-MSDU

Beamforming sounding

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

DL MU PPDU multi-tone

HE NDP

LDPC Tx

LDPC Rx

Individual Target Wake Time

#### Wi-Fi CERTIFIED 6® Release 2 (continued)

MCS 10-11 Rx

MCS 10-11 Tx

MCS 8-9 Rx

MCS 8-9 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

MU-RTS Trigger frame

Operating mode control field

Operating mode subfield in A-Control field

Operating mode indication

SU beamformee

SU-MIMO

**UL OFDMA** 

UL TB PPDU multi-tone

Wi-Fi 6E

Multiple M-BSSID

Wi-Fi 6 Release 2 features

**UL MU-MIMO** 

UL MU Control

Target Wake Time information frames

Broadcast Target Wake Time

Dynamic MU SMPS

M-BSSID control frames

Preamble Puncturing

#### Wi-Fi CERTIFIED 7™

Advertised TID-to-link mapping

A-MPDU with A-MSDU

Beamforming sounding

BSS critical update

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

Compressed Block Ack Rx (buffer size 512)

Compressed Block Ack Tx (buffer size 512)



**Certification ID: WFA131572** 



Role: Station Page 5 of 5

## Wi-Fi CERTIFIED 7™ (continued)

DL MU-MIMO

Dynamic MU SMPS

EMLSR (Enhanced Multilink Single-Radio)

LDPC Rx

LDPC Tx

Load Balancing in MLO

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MCS 12-13 Rx

MCS 12-13 Tx

Multi-link reconfiguration - AP removal

Multi-link reconfiguration - AP restart

Multi-RU

Operating mode indication

Operating mode indication for 320 MHz

Static puncturing

SU-MIMO

Triggered uplink access optimization

UL MU-MIMO

**UL OFDMA** 

# Wi-Fi CERTIFIED™ ac (continued)

SU beamformee

#### Wi-Fi CERTIFIED™ b

## Wi-Fi CERTIFIED™ g

#### Wi-Fi CERTIFIED™ n

A-MPDU Tx

**OBSS** on Extension Channel

**Power Management** 

Short Guard Interval

STBC

## Wi-Fi Enhanced Open™ 2023-12

## Wi-Fi QoS Management™

Default DSCP to UP mapping

DSCP QoS Map

Mirrored Stream Classification Service

#### Wi-Fi CERTIFIED™ a

#### Wi-Fi CERTIFIED™ ac

Extended 5 GHz Channel Support

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

MCS 8-9 Rx

Short Guard Interval

STBC

LDPC Tx