



Wi-Fi CERTIFIED™ Certificate



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA131909

Product Info

| | |
|------------------------------|---|
| Date of Certification | November 22, 2024 |
| Company | Zyxel Communications Corporation |
| Product Name | 5G NR Indoor Router |
| Product Model Variant | NR5309 |
| Model Number | NR5309 |
| Category | Routers |
| Sub-category | Access Point for Home or Small Office (Wireless Router) |

Summary of Certifications

| CLASSIFICATION | CERTIFICATION |
|---------------------|---|
| Access | Wi-Fi Protected Setup™ |
| Connectivity | 2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n |
| Optimization | WMM® Wi-Fi Agile Multiband™ |
| Security | Protected Management Frames WPA2™-Personal 2021-01 WPA3™-Personal 2023-12 |



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA131909



Role: Access Point

Page 2 of 3

Wi-Fi Components

Wi-Fi Component Operating System

Linux Kernel 5.4.194

Wi-Fi Component Firmware

0x8a00

RF Architecture

| Bands Supported | Transmit (Tx) | Receive (Rx) |
|-----------------|---------------|--------------|
| 2.4 GHz | 2 | 2 |
| 5 GHz | 2 | 2 |

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz
40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz
160 MHz Channel Width in 5 GHz

Protected Management Frames

WMM®

WPA2™-Personal 2021-01

WPA3™-Personal 2023-12

Wi-Fi Agile Multiband™

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU

Wi-Fi CERTIFIED 6® (continued)

Basic Trigger frame in HE MU PPDU
BSRP Trigger frame
Compressed Block Ack Rx (buffer size 256)
Compressed Block Ack Tx (buffer size 256)
DL MU-MIMO
DL OFDMA
Individual Target Wake Time
LDPC Rx
LDPC Tx
MCS 8-9 Rx
MCS 8-9 Tx
MCS 10-11 Rx
MCS 10-11 Tx
MU EDCA Parameter Set element
MU-BAR Trigger frame
MU-RTS Trigger frame
Operating mode indication
SU beamformer
SU-MIMO
TXOP RTS Threshold
UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA131909



Role: Access Point

Page 3 of 3

Wi-Fi CERTIFIED™ ac (continued)

A-MPDU with A-MSDU
DL MU-MIMO
LDPC Rx
LDPC Tx
MCS 8-9 Rx
Short Guard Interval
STBC
SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx
HT Duplicate Mode
OBSS on Extension Channel
Short Guard Interval
STBC

Wi-Fi Protected Setup™

PIN
Pushbutton