



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

**Certification ID: WFA132322** 

## **Product Info**

Date of Certification August 22, 2024

**Company** Huawei Technologies Co., Ltd.

Product Name Wireless LAN Access Point

Product Model Variant eKitEngine 6760S-56

Model Number eKitEngine 6760S-56

**Category** Routers

**Sub-category** Enterprise/Service Provider Access Point, Switch/Controller or Router

# **Summary of Certifications**

CLASSIFICATION CERTIFICATION

Access Wi-Fi Protected Setup™

**Connectivity** 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities

Wi-Fi CERTIFIED 6®
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n

**Optimization** WMM®

Wi-Fi Agile Multiband™ Wi-Fi EasyMesh™

Security Protected Management Frames

WPA2<sup>™</sup>-Enterprise 2018-04 WPA2<sup>™</sup>-Personal 2021-01 WPA3<sup>™</sup>-Enterprise 2020-02 WPA3<sup>™</sup>-Personal 2020-12

Spectrum & Regulatory

**Features** 

Spectrum & Regulatory



Certification ID: WFA132322



Role: Access Point Page 2 of 4

Wi-Fi Components

**Wi-Fi Component Operating System** 

Linux

Wi-Fi Component Firmware

V5

**RF Architecture** 

Bands Supported Transmit (Tx) Receive (Rx)

2.4 GHz 4

5 GHz 4 4

**Certifications** 

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz

40 MHz Channel Width in 2.4 GHz

WPA3™-Enterprise 2020-02

WPA2™-Personal 2021-01

EAP methods

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz

40 MHz Channel Width in 5 GHz

80 MHz Channel Width in 5 GHz

160 MHz Channel Width in 5 GHz

WPA3™-Personal 2020-12

Wi-Fi Agile Multiband™

Automatically populate BSS Transition candidate list

Cellular Data aware

**Protected Management Frames** 

**Spectrum & Regulatory** 

802.11d

802.11h

4 antenna support

A-MPDU with A-MSDU

Wi-Fi CERTIFIED 6®

Basic Trigger frame in HE MU PPDU

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

DL OFDMA

Individual Target Wake Time

LDPC Rx

**WMM®** 

WPA2™-Enterprise 2018-04

EAP methods





**Certification ID: WFA132322** 

Role: Access Point Page 3 of 4

### Wi-Fi CERTIFIED 6® (continued)

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

MU-RTS Trigger frame

Operating mode indication

SU beamformer

SU-MIMO

UL OFDMA

## Wi-Fi CERTIFIED™ n (continued)

A-MPDU Tx

HT Duplicate Mode

**OBSS** on Extension Channel

Short Guard Interval

STBC

## Wi-Fi Protected Setup™

PIN

Pushbutton

#### Wi-Fi CERTIFIED™ a

#### Wi-Fi CERTIFIED™ ac

RTS with BW Signaling

Extended 5 GHz Channel Support

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

LDPC Tx

MCS 8-9 Rx

Short Guard Interval

STBC

SU beamformer

### Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n





**Certification ID: WFA132322** 

Role: Controller

Wi-Fi Components

Wi-Fi Component Operating System

Linux

Certifications

Wi-Fi EasyMesh™