



# Wi-Fi CERTIFIED™ Certificate



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: [www.wi-fi.org/certification/programs](http://www.wi-fi.org/certification/programs)

**Certification ID: WFA120766**

## Product Info

<b>Date of Certification</b>	September 5, 2024
<b>Company</b>	CradlePoint, Inc.
<b>Product Name</b>	R920-C7A Ruggedized Router
<b>Product Model Variant</b>	Updating Testing Modules
<b>Model Number</b>	S5A235A
<b>Category</b>	Routers
<b>Sub-category</b>	Access Point for Home or Small Office (Wireless Router)

## Summary of Certifications

<b>CLASSIFICATION</b>	<b>CERTIFICATION</b>
<b>Connectivity</b>	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n
<b>Optimization</b>	WMM® Wi-Fi Agile Multiband™
<b>Security</b>	Protected Management Frames WPA2™-Enterprise 2018-04 WPA2™-Personal 2021-01 WPA3™-Enterprise 2020-02 WPA3™-Personal 2020-12
<b>Spectrum &amp; Regulatory Features</b>	Spectrum & Regulatory



# Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA120766



Role: Access Point

Page 2 of 3

## Wi-Fi Components

### Wi-Fi Component Operating System

Linux

### Wi-Fi Component Firmware

WLAN.HK.2.5.r4-00745-  
QCAHKSWPL\_SILICONZ-1 v1

### RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2

## Certifications

### 2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz  
40 MHz Channel Width in 2.4 GHz

### 5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz  
40 MHz Channel Width in 5 GHz  
80 MHz Channel Width in 5 GHz

### Protected Management Frames

### Spectrum & Regulatory

802.11d  
802.11h

### WMM®

### WPA2™-Enterprise 2018-04

EAP methods

### WPA2™-Personal 2021-01

### WPA3™-Enterprise 2020-02

EAP methods

### WPA3™-Personal 2020-12

### Wi-Fi Agile Multiband™

### Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU  
Basic Trigger frame in HE MU PPDU  
BSRP Trigger frame  
Compressed Block Ack Rx (buffer size 256)  
Compressed Block Ack Tx (buffer size 256)  
DL OFDMA  
Individual Target Wake Time  
LDPC Rx  
LDPC Tx  
MCS 8-9 Rx  
MCS 8-9 Tx  
MCS 10-11 Rx  
MCS 10-11 Tx  
MU EDCA Parameter Set element



# Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA120766



Role: Access Point

Page 3 of 3

## Wi-Fi CERTIFIED 6® (continued)

MU-BAR Trigger frame  
MU-RTS Trigger frame  
Operating mode indication  
SU beamformer  
SU-MIMO  
TXOP RTS Threshold  
UL OFDMA

## Wi-Fi CERTIFIED™ a

## Wi-Fi CERTIFIED™ ac

RTS with BW Signaling  
Extended 5 GHz Channel Support  
A-MPDU with A-MSDU  
LDPC Rx  
LDPC Tx  
MCS 8-9 Rx  
Short Guard Interval  
STBC  
SU beamformer

## Wi-Fi CERTIFIED™ b

## Wi-Fi CERTIFIED™ g

## Wi-Fi CERTIFIED™ n

A-MPDU Tx  
OBSS on Extension Channel  
Short Guard Interval  
STBC