

## Wi-Fi CERTIFIED™ Certificate



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

**Certification ID: WFA132707** 

#### **Product Info**

**Date of Certification** September 16, 2024

**Company** Zyxel Communications Corporation

Product Name Dual-Band Wireless AX3000 Gigabit Ethernet IAD

Product Model Variant EX3501-T2

Model Number EX3501-T2

**Category** Routers

**Sub-category** Cable, DSL or Other Broadband Gateway (Integrated Home Access

Device)

### **Summary of Certifications**

CLASSIFICATION CERTIFICATION

Access Wi-Fi Protected Setup™

**Connectivity** 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities

Wi-Fi CERTIFIED 6®
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n

**Optimization** WMM®

Wi-Fi Agile Multiband™

Security Protected Management Frames

WPA2<sup>™</sup>-Personal 2021-01 WPA3<sup>™</sup>-Personal 2022-06



## Wi-Fi CERTIFIED™ Certificate



**Certification ID: WFA132707** 

| Role: Access Point | Page 2 of 3 |
|--------------------|-------------|
|                    |             |

Wi-Fi Components

**Wi-Fi Component Operating System** 

Linux 4.4.115

Wi-Fi Component Firmware

7.6.2.3

#### **RF Architecture**

| Bands Supported | Transmit (Tx) | Receive (Rx) |
|-----------------|---------------|--------------|
| 2.4 GHz         | 2             | 2            |
| 5 GHz           | 2             | 2            |

#### Certifications

#### 2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz 40 MHz Channel Width in 2.4 GHz

#### **5 GHz Spectrum Capabilities**

20 MHz Channel Width in 5 GHz 40 MHz Channel Width in 5 GHz 80 MHz Channel Width in 5 GHz 160 MHz Channel Width in 5 GHz

#### **Protected Management Frames**

**WMM®** 

WPA2™-Personal 2021-01

WPA3™-Personal 2022-06

Wi-Fi Agile Multiband™

#### Wi-Fi CERTIFIED 6® (continued)

Basic Trigger frame in HE MU PPDU

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

DL OFDMA

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

MU-RTS Trigger frame

Operating mode indication

SU beamformer

SU-MIMO

TXOP RTS Threshold

**UL OFDMA** 

#### Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU

#### Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac



# **Wi-Fi CERTIFIED™ Certificate**



**Certification ID: WFA132707** 

| Role: Access Point              |
|---------------------------------|
| Wi-Fi CERTIFIED™ ac (continued) |
| RTS with BW Signaling           |
| A-MPDU with A-MSDU              |
| DL MU-MIMO                      |
| LDPC Rx                         |
| LDPC Tx                         |
| MCS 8-9 Rx                      |
| Short Guard Interval            |
| STBC                            |
| SU beamformer                   |
|                                 |
| Wi-Fi CERTIFIED™ b              |
| WHI I OLIXIII ILD D             |
| Wi-Fi CERTIFIED™ g              |
| Wi-Fi CERTIFIED™ n              |
| A-MPDU Tx                       |
| HT Duplicate Mode               |
| OBSS on Extension Channel       |
| Short Guard Interval            |
| STBC                            |
|                                 |
| Wi Ei Protected SetunIM         |
| Wi-Fi Protected Setup™          |
| PIN                             |
| Pushbutton                      |