Wi-Fi CERTIFIED™ Certificate

This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA115016

Product Info

Date of Certification	February 4, 2025
Company	Robert Bosch GmbH
Product Name	Cockpit Solution
Product Model Variant	MY26
Model Number	GM VCU 1.1
Category	Other
Sub-category	In-vehicle Network

Summary of Certifications

CLASSIFICATION	CERTIFICATION
Access	Passpoint® Release 3
Network management	WMM® Wi-Fi Agile Multiband™
Security	Protected Management Frames WPA2™-Enterprise 2018-04 WPA2™-Personal 2018-04 WPA2™-Personal 2021-01 WPA3™-Personal 2020-12
Wi-Fi (MAC/PHY)	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n

Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA115016

Wi-Fi Components

Wi-Fi Component Operating System

Android U

Wi-Fi Component Firmware

1.0.2.0.3920.0

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz

Protected Management Frames

WMM®

WPA2™-Personal 2021-01

WPA3™-Personal 2020-12

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU
Compressed Block Ack Rx (buffer size 256)
LDPC Rx
LDPC Tx
MCS 8-9 Rx

Wi-Fi CERTIFIED 6® (continued)

MCS 8-9 Tx
MCS 10-11 Rx
MCS 10-11 Tx
SU-MIMO
TXOP RTS Threshold

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

RTS with BW Signaling
A-MPDU with A-MSDU
LDPC Rx
LDPC Tx
MCS 8-9 Rx
Short Guard Interval
STBC

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

Wi-Fi CERTIFIED™ n (continued)

OBSS on Extension Channel

Short Guard Interval

STBC

A-MPDU Tx

Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA115016

Wi-Fi Components

Wi-Fi Component Operating System

Android U

Wi-Fi Component Firmware

1.0.2.0.3920.0

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz

Passpoint® Release 3

Online Sign Up and Policy provisioning
Online Sign Up using single SSID
Venue Information
Terms and Conditions
Roaming Consortium Selection

Protected Management Frames

WMM®

WPA2™-Enterprise 2018-04

WPA2™-Enterprise 2018-04 (continued)

EAP methods
　EAP TLS
　EAP TTLS

WPA2™-Personal 2018-04

WPA3™-Personal 2020-12

Wi-Fi Agile Multiband™

ANQP
ANQP-based Neighbor report
Beacon Report Measurement Active Mode
Beacon Report Measurement Passive Mode
BTM Query
Cellular Data capable

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU
Beamforming sounding
BSRP Trigger frame
Compressed Block Ack Rx (buffer size 256)

Wi-Fi CERTIFIED 6® (continued)

Compressed Block Ack Tx (buffer size 256)
DL MU-MIMO
LDPC Rx
LDPC Tx
MCS 8-9 Rx
MCS 8-9 Tx
MCS 10-11 Rx
MCS 10-11 Tx
MU EDCA Parameter Set element
MU-BAR Trigger frame
MU-RTS Trigger frame
M-BSSID
Operating mode control field
Operating mode subfield in A-Control field
Operating mode indication
SU beamformee
SU-MIMO
UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

RTS with BW Signaling
A-MPDU with A-MSDU
DL MU-MIMO
LDPC Rx
MCS 8-9 Rx
Short Guard Interval
STBC
LDPC Tx
SU beamformee

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

STBC
A-MPDU Tx
OBSS on Extension Channel
Power Management
Short Guard Interval