



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

# Certification ID: WFA123248

## **Product Info**

Date of Certification	October 1, 2024
Company	NXP Semiconductors
Product Name	9098
Product Model Variant	9098-R10.12_G
Model Number	9098
Category	Other
Sub-category	Embedded Module

## **Summary of Certifications**

CLASSIFICATION	CERTIFICATION
Access	Wi-Fi Protected Setup™
Connectivity	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n Wi-Fi Direct®
Optimization	WMM® Wi-Fi Agile Multiband™
Security	Protected Management Frames WPA2™-Personal 2021-01 WPA3™-Personal 2023-12
Spectrum & Regulatory Features	Spectrum & Regulatory



# Wi-Fi CERTIFIED<sup>™</sup> Certificate



# **Certification ID: WFA123248**

Role: Access Point		Page 2 of 5	
Wi-Fi Components			
Wi-Fi Component Operating System	<b>RF Architecture</b>		
Linux	Bands Supported	Transmit (Tx)	Receive (Rx)
Wi-Fi Component Firmware p149.50	2.4 GHz	2	2
	5 GHz	2	2

#### Certifications

2.4 GHz Spectrum Capabilities	WPA3™-Personal 2023-12
20 MHz Channel Width in 2.4 GHz 40 MHz Channel Width in 2.4 GHz	Wi-Fi CERTIFIED 6®
<b>5 GHz Spectrum Capabilities</b> 20 MHz Channel Width in 5 GHz 40 MHz Channel Width in 5 GHz 80 MHz Channel Width in 5 GHz	A-MPDU with A-MSDU LDPC Rx LDPC Tx MCS 8-9 Rx MCS 8-9 Tx MCS 10-11 Rx MCS 10-11 Tx SU beamformer
Protected Management Frames	
Spectrum & Regulatory	Wi-Fi CERTIFIED™ a
802.11d	Wi-Fi CERTIFIED™ ac
802.11h	A-MPDU with A-MSDU Extended 5 GHz Channel Support
WMM®	LDPC Rx
Max Throughput	LDPC Tx MCS 8-9 Rx RTS with BW Signaling
WPA2™-Personal 2021-01	Short Guard Interval SU beamformer



**Certification ID: WFA123248** 



### **Role: Access Point**

# Page 3 of 5

Wi-Fi CERTIFIED™ b

#### Wi-Fi CERTIFIED™ g

#### Wi-Fi CERTIFIED™ n

HT Duplicate Mode OBSS on Extension Channel Short Guard Interval A-MPDU Tx

#### Wi-Fi Protected Setup™

PIN

Pushbutton



Certification ID: WFA123248



#### **Role: Station** Page 4 of 5 **Wi-Fi Components** Wi-Fi Component Operating System **RF** Architecture Linux Bands Supported Transmit (Tx) Receive (Rx) Wi-Fi Component Firmware 2.4 GHz 2 2 p149.50 5 GHz 2 2

#### Certifications

#### 2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz 40 MHz Channel Width in 2.4 GHz

#### **5 GHz Spectrum Capabilities**

20 MHz Channel Width in 5 GHz 40 MHz Channel Width in 5 GHz 80 MHz Channel Width in 5 GHz

#### **Protected Management Frames**

#### Spectrum & Regulatory

802.11d 802.11h

#### WMM®

Max Throughput

WPA2<sup>™</sup>-Personal 2021-01

#### WPA3<sup>™</sup>-Personal 2023-12

#### Wi-Fi Agile Multiband™

ANQP

BTM Query Cellular Data capable

#### Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU Beamforming sounding BSRP Trigger frame Compressed Block Ack Rx (buffer size 256) Compressed Block Ack Tx (buffer size 256) DL MU-MIMO DL MU PPDU multi-tone HE NDP LDPC Tx LDPC Rx MCS 10-11 Rx MCS 10-11 Tx MCS 8-9 Rx MCS 8-9 Tx MU EDCA Parameter Set element **MU-BAR Trigger frame** 



Certification ID: WFA123248



# **Role: Station**

## Page 5 of 5

# Wi-Fi CERTIFIED 6® (continued) Wi-Fi Direct® (continued) MU-RTS Trigger frame Wi-Fi Direct with WPA2 Operating mode indication SU beamformee Wi-Fi Protected Setup™ SU-MIMO UL OFDMA PIN UL TB PPDU multi-tone Pushbutton Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Extended 5 GHz Channel Support RTS with BW Signaling A-MPDU with A-MSDU DL MU-MIMO LDPC Rx MCS 8-9 Rx Short Guard Interval LDPC Tx SU beamformee Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n A-MPDU Tx **OBSS** on Extension Channel **Power Management** Short Guard Interval Wi-Fi Direct®