



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA132882

Product Info

Date of Certification October 21, 2024

Company Arista Networks, Inc.

Product Name Arista Wi-Fi 7 Indoor Access Point

Product Model Variant Indoor AP with integrated antennas

Model Number C-460

Category Routers

Sub-category Enterprise/Service Provider Access Point, Switch/Controller or Router

Summary of Certifications

CLASSIFICATION CERTIFICATION

Connectivity 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities6 GHz Spectrum CapabilitiesWi-Fi CERTIFIED 6® Release 2

Wi-Fi CERTIFIED 7™ Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n

Wi-Fi Enhanced Open™ 2023-12

Optimization WMM®

Wi-Fi Agile Multiband™

Security Protected Management Frames

WPA2[™]-Enterprise 2018-04 WPA2[™]-Personal 2021-01 WPA3[™]-Enterprise 2022-12 WPA3[™]-Personal 2023-12

Spectrum & Regulatory

Features

Spectrum & Regulatory

This certificate was downloaded on 2025-05-01 at 04:42:54 UTC



Certification ID: WFA132882



Role: Access Point		Page 2 of 4		
Wi-Fi Components				
Wi-Fi Component Operating System	RF Architecture			
Wi-Fi Component Firmware IPQ9574.WFA.12.3.r4-00134-P-1	Bands Supported	Transmit (Tx)	Receive (Rx)	
	2.4 GHz	4	4	
	5 GHz	4	4	
		•		
	6 GHz	4	4	
Certifications				
	0	1-1/	-D	
2.4 GHz Spectrum Capabilities	Spectrum & Regu	latory (continue	d)	
20 MHz Channel Width in 2.4 GHz 802.11d				
40 MHz Channel Width in 2.4 GHz	802.11h			
5 GHz Spectrum Capabilities	WMM®			
20 MHz Channel Width in 5 GHz	WPA2™-Enterpris	se 2018-04		
40 MHz Channel Width in 5 GHz	W / L Lintorprite	WI AZ Eliterprise 2010 04		
80 MHz Channel Width in 5 GHz 160 MHz Channel Width in 5 GHz	EAP methods			
100 WHZ CHAINEI WIGHT III 3 OHZ	WD A GTW D		_	
6 GHz Spectrum Capabilities	WPA2™-Personal	2021-01		
	WPA3™-Enterpris	se 2022-12		
20 MHz Channel Width in 6 GHz 40 MHz Channel Width in 6 GHz	EAP methods			
80 MHz Channel Width in 6 GHz	192-bit security			
160 MHz Channel Width in 6 GHz	Fast Transition OTA on	Fast Transition OTA on WPA3-Enterprise		

Spectrum & Regulatory

Protected Management Frames

320 MHz channel width in 6 GHz

Fast Transition OTA on WPA3-Enterprise transition mode

Fast Transition OTDS on WPA3-Enterprise

WPA3™-Personal 2023-12



Certification ID: WFA132882



Role: Access Point Page 3 of 4

WPA3™-Personal 2023-12 (continued)

AKM 24

AKM 25

Fast Transition OTA on WPA3-Personal

Fast Transition OTA on WPA3-Personal transition mode

Fast Transition OTDS on WPA3-Personal

Beacon Protection

SAE-Public Key

Operating Channel Validation

Wi-Fi Agile Multiband™

Automatically populate BSS Transition candidate list

Cellular Data aware

Fast Transition OTA on WPA2-Enterprise

Fast Transition OTA on WPA2-Personal

Wi-Fi CERTIFIED 6® Release 2

4 antenna support

A-MPDU with A-MSDU

Basic Trigger frame in HE MU PPDU

Beamforming sounding

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

DL OFDMA

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

Wi-Fi CERTIFIED 6® Release 2 (continued)

MU-BAR Trigger frame

MU-RTS Trigger frame

M-BSSID

Operating mode subfield in A-Control field

Operating mode indication

Operating mode UL MU Rx

SU beamformer

SU-MIMO

TXOP RTS Threshold

UL OFDMA

Wi-Fi 6E

Co-located BSS

Multiple M-BSSID

Wi-Fi 6 Release 2 features

UL MU-MIMO

UL MU Control

UL Extended Range

Target Wake Time information frames

Broadcast Target Wake Time

Extended sleep

Dynamic MU SMPS

M-BSSID control frames

Wi-Fi CERTIFIED 7™

Advertised TID-to-link mapping

A-MPDU with A-MSDU

Beamforming sounding

BSRP Trigger frame

BSS critical update

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

Compressed Block Ack Rx (buffer size 512)

Compressed Block Ack Tx (buffer size 512)

DL MU-MIMO



Certification ID: WFA132882



Role: Access Point Page 4 of 4

Wi-Fi CERTIFIED 7™ (continued)

DL OFDMA

Dynamic MU SMPS

EMLSR (Enhanced Multilink Single-Radio)

EPCS (Emergency Preparedness Communications Services)

priority access

LDPC Rx

LDPC Tx

Load Balancing in MLO

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MCS 12-13 Rx

MCS 12-13 Tx

Multi-link reconfiguration - AP removal

Multi-link reconfiguration - AP restart

Multi-RU

MU-RTS Trigger frame

Operating mode indication

Operating mode indication for 320 MHz

Static puncturing

STR (Simultaneous Transmit and Receive)

SU-MIMO

Triggered uplink access optimization

UL MU-MIMO

UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU

DL MU-MIMO

Extended 5 GHz Channel Support

LDPC Rx

Wi-Fi CERTIFIED™ ac (continued)

LDPC Tx

MCS 8 Rx

MCS 8-9 Rx

RTS with BW Signaling

Short Guard Interval

STBC

SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx

HT Duplicate Mode

OBSS on Extension Channel

RIFS

Short Guard Interval

STBC

Wi-Fi Enhanced Open™ 2023-12