Wi-Fi CERTIFIED™ Certificate

This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA132967

Product Info

Date of Certification	February 25, 2025
Company	Huawei Technologies Co., Ltd.
Product Name	Optical Network Terminal
Product Model Variant	OptiXstar HN8546X6-70
Model Number	OptiXstar HN8546X6-70
Category	Routers
Sub-category	Cable, DSL or Other Broadband Gateway (Integrated Home Access Device)

Summary of Certifications

CLASSIFICATION	CERTIFICATION
Access	Wi-Fi Protected Setup™
Connectivity	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Release 2 Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n
Optimization	WMM® WMM®-Power Save Wi-Fi Agile Multiband™ Wi-Fi EasyMesh™
Security	Protected Management Frames WPA2™-Enterprise 2018-04 WPA2™-Personal 2021-01 WPA3™-Enterprise 2022-12 WPA3™-Personal 2023-12

Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA132967

CLASSIFICATION	CERTIFICATION
Spectrum & Regulatory Features	Spectrum & Regulatory

Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA132967

Wi-Fi Components

Wi-Fi Component Operating System
Linux

Wi-Fi Component Firmware
V500

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz
40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz
160 MHz Channel Width in 5 GHz

Protected Management Frames

Spectrum & Regulatory

802.11d
802.11h

WMM®

WMM®-Power Save

WPA2™-Enterprise 2018-04

WPA2™-Enterprise 2018-04 (continued)

EAP methods

WPA2™-Personal 2021-01

WPA3™-Enterprise 2022-12

EAP methods
192-bit security

WPA3™-Personal 2023-12

Wi-Fi Agile Multiband™

Wi-Fi CERTIFIED 6® Release 2

A-MPDU with A-MSDU
Basic Trigger frame in HE MU PPDU
BSRP Trigger frame
Compressed Block Ack Rx (buffer size 256)
Compressed Block Ack Tx (buffer size 256)
DL MU-MIMO
DL OFDMA
Individual Target Wake Time

Wi-Fi CERTIFIED 6® Release 2 (continued)

LDPC Rx
LDPC Tx
MCS 8-9 Rx
MCS 8-9 Tx
MCS 10-11 Rx
MCS 10-11 Tx
MU EDCA Parameter Set element
MU-BAR Trigger frame
MU-RTS Trigger frame
Operating mode subfield in A-Control field
Operating mode indication
Operating mode UL MU Rx
SU beamformer
SU-MIMO
TXOP RTS Threshold
UL OFDMA
Wi-Fi 6 Release 2 features
    Dynamic MU SMPS

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU
DL MU-MIMO
LDPC Rx
LDPC Tx
MCS 8-9 Rx
RTS with BW Signaling
Short Guard Interval
STBC
SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx
HT Duplicate Mode
OBSS on Extension Channel
Short Guard Interval
STBC

Wi-Fi Protected Setup™

PIN
Pushbutton

Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA132967

Wi-Fi Components

Wi-Fi Component Operating System

Linux

Certifications

Wi-Fi EasyMesh™