



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

## **Certification ID: WFA133170**

#### **Product Info**

**Date of Certification** May 9, 2025

**Company** Sony Group Corporation

Product Name ONU INTEGRATED HIGH-SPEED ROUTER

Product Model Variant NSD-G3100T

Model Number NSD-G3100T

**Category** Routers

**Sub-category** Access Point for Home or Small Office (Wireless Router)

### **Summary of Certifications**

CLASSIFICATION CERTIFICATION

Alternative topologies Wi-Fi EasyMesh™

Network management WMM®

Wi-Fi Agile Multiband™

Security Protected Management Frames

WPA2<sup>™</sup>-Personal 2021-01 WPA3<sup>™</sup>-Personal 2024-10 Wi-Fi Enhanced Open<sup>™</sup> 2023-12

Wi-Fi (MAC/PHY) 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities6 GHz Spectrum Capabilities

Spectrum & Regulatory

Wi-Fi CERTIFIED 6® Release 2

Wi-Fi CERTIFIED 7™
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ ac
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n



**Certification ID: WFA133170** 



Role: Access Point		Pa	Page 2 of 5	
Wi-Fi Components				
Wi-Fi Component Operating System	RF Architecture			
Wi-Fi Component Firmware	Bands Supported	Transmit (Tx)	Receive (Rx)	
	2.4 GHz	4	4	
V8.0	5 GHz	4	4	
	6 GHz	4	4	
Certifications				
2.4 GHz Spectrum Capabilities	Spectrum & Regulatory (continued)			
20 MHz Channel Width in 2.4 GHz	802.11d			
40 MHz Channel Width in 2.4 GHz	802.11h			
5 GHz Spectrum Capabilities	<b>WMM</b> ®			
20 MHz Channel Width in 5 GHz	WPA2™-Personal 2021-01			
40 MHz Channel Width in 5 GHz 80 MHz Channel Width in 5 GHz	WPA3™-Person	al 2024-10		
160 MHz Channel Width in 5 GHz	Wi As -i cison	ui 2024-10		
	AKM 24  Beacon Protection			
6 GHz Spectrum Capabilities	Boacon Fotostion			
20 MHz Channel Width in 6 GHz	Wi-Fi Agile Multiband™			
40 MHz Channel Width in 6 GHz				
80 MHz Channel Width in 6 GHz 160 MHz Channel Width in 6 GHz	Wi-Fi CERTIFIED	) 6® Release 2		
320 MHz channel width in 6 GHz	4 antenna support			
	A-MPDU with A-MSD			
Protected Management Frames		Basic Trigger frame in HE MU PPDU		
	Beamforming soundir  BSRP Trigger frame	9		
Spectrum & Regulatory		ck Rx (buffer size 256)		



**Certification ID: WFA133170** 



Role: Access Point Page 3 of 5

#### Wi-Fi CERTIFIED 6® Release 2 (continued)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

DL OFDMA

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

MU-RTS Trigger frame

M-BSSID

Operating mode subfield in A-Control field

Operating mode indication

Operating mode UL MU Rx

SU beamformer

SU-MIMO

TXOP RTS Threshold

**UL OFDMA** 

Wi-Fi 6E

Wi-Fi 6 Release 2 features

UL MU-MIMO

Dynamic MU SMPS

#### Wi-Fi CERTIFIED 7™ (continued)

Compressed Block Ack Tx (buffer size 512)

DL MU-MIMO

DL OFDMA

Dynamic MU SMPS

EMLSR (Enhanced Multilink Single-Radio)

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MCS 12-13 Rx

MCS 12-13 Tx

Multi-RU

MU-RTS Trigger frame

Operating mode indication

Operating mode indication for 320 MHz

Static puncturing

STR (Simultaneous Transmit and Receive)

SU-MIMO

Triggered uplink access optimization

UL MU-MIMO

**UL OFDMA** 

#### Wi-Fi CERTIFIED™ a

#### Wi-Fi CERTIFIED 7™

A-MPDU with A-MSDU

Beamforming sounding

BSRP Trigger frame

BSS critical update

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

Compressed Block Ack Rx (buffer size 512)

### Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

LDPC Tx

MCS 8-9 Rx

Short Guard Interval

STBC



**Certification ID: WFA133170** 



Role: Access Point	Page 4 of 5
Wi-Fi CERTIFIED™ ac (continued)	
SU beamformer	
Wi-Fi CERTIFIED™ b	
Wi-Fi CERTIFIED™ g	
Wi-Fi CERTIFIED™ n	
A-MPDU Tx	
OBSS on Extension Channel	
Short Guard Interval	
STBC	



**Certification ID: WFA133170** 



Role: Controller

Wi-Fi Components

Wi-Fi Component Operating System

Linux

Certifications

Wi-Fi EasyMesh™