



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA133203

Product Info

Date of Certification October 28, 2024

Company Huawei Technologies Co., Ltd.

Product Name Optical Network Terminal

Product Model Variant OptiXstar W826P

Model Number OptiXstar W826P

Category Routers

Sub-category Cable, DSL or Other Broadband Gateway (Integrated Home Access

Device)

Summary of Certifications

Access Wi-Fi Protected Setup™

Connectivity 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities

Wi-Fi CERTIFIED 6®
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n

Optimization WMM®

WMM®-Power Save Wi-Fi Agile Multiband™ Wi-Fi EasyMesh™

Security Protected Management Frames

WPA2[™]-Enterprise 2018-04 WPA2[™]-Personal 2021-01 WPA3[™]-Enterprise 2020-02 WPA3[™]-Personal 2020-12





Certification ID: WFA133203

Role: Access Point	Page 2 of 4

Wi-Fi Components

Wi-Fi Component Operating System

Linux

Wi-Fi Component Firmware

V5

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz 40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz 40 MHz Channel Width in 5 GHz 80 MHz Channel Width in 5 GHz 160 MHz Channel Width in 5 GHz

WPA2™-Personal 2021-01

WPA3[™]-Enterprise 2020-02

EAP methods

WPA3™-Personal 2020-12

Wi-Fi Agile Multiband™

Automatically populate BSS Transition candidate list

Protected Management Frames

WMM®

WMM®-Power Save

Legacy Power Save Unschedule auto PS

WPA2™-Enterprise 2018-04

EAP methods

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU

Basic Trigger frame in HE MU PPDU

BSRP Trigger frame

DL MU-MIMO

DL OFDMA

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx





Certification ID: WFA133203

Role: Access Point Page 3 of 4

Wi-Fi CERTIFIED 6® (continued)

MCS 10-11 Tx

MU-BAR Trigger frame

MU-RTS Trigger frame

Operating mode indication

SU beamformer

UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

RTS with BW Signaling

Extended 5 GHz Channel Support

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

LDPC Tx

MCS 8-9 Rx

Short Guard Interval

STBC

SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx

OBSS on Extension Channel

Short Guard Interval

STBC

Wi-Fi EasyMesh™

Wi-Fi EasyMesh™ (continued)

Backhaul Link

Backhaul in 2.4 GHz

Backhaul in 5 GHz low band

Backhaul in 5 GHz high band

Backhaul over Ethernet

Fronthaul Access Point

Fronthaul in 2.4 GHz

Fronthaul in 5 GHz low band

Fronthaul in 5 GHz high band

Client Capability Query

Unassociated STA Link Metrics Reporting

Backhaul onboarding with Wi-Fi Protected Setup pushbutton

Coordinated CAC

Traffic separation

Wi-Fi Protected Setup™

PIN

Pushbutton





Certification ID: WFA133203

Role: Controller

Wi-Fi Components

Wi-Fi Component Operating System

Linux

Certifications

Wi-Fi EasyMesh™