



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

# **Certification ID: WFA133221**

# **Product Info**

**Date of Certification** March 7, 2025

Company FURUNO SYSTEMS Co., Ltd.

Product Name ACERA EW750

Product Model Variant New Product Model

Model Number WN-750

Category Routers

**Sub-category** Enterprise/Service Provider Access Point, Switch/Controller or Router

# **Summary of Certifications**

CLASSIFICATION	CERTIFICATION

**Connectivity** 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities6 GHz Spectrum CapabilitiesWi-Fi CERTIFIED 6® Release 2

Wi-Fi CERTIFIED 7™ Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n

Wi-Fi Enhanced Open™ 2023-12

**Optimization** WMM®

Wi-Fi Agile Multiband™

**Security** Protected Management Frames

WPA2<sup>™</sup>-Enterprise 2018-04 WPA2<sup>™</sup>-Personal 2021-01 WPA3<sup>™</sup>-Enterprise 2022-12 WPA3<sup>™</sup>-Personal 2024-10

Spectrum & Regulatory

**Features** 

Spectrum & Regulatory



**Certification ID: WFA133221** 



Role: Access Point	Role: Access Point			
Wi-Fi Components				
Wi-Fi Component Operating System	RF Architecture			
Wi-Fi Component Firmware 1.00	Bands Supported	Transmit (Tx)	Receive (Rx)	
	2.4 GHz	2	2	
	5 GHz	2	2	
Wi-Fi Component Operating System	RF Architecture			
Wi-Fi Component Firmware 1.00	Bands Supported	Transmit (Tx)	Receive (Rx)	
	2.4 GHz	2	2	
	5 GHz	2	2	
	6 GHz	2	2	
Certifications  2.4 GHz Spectrum Capabilities	6 GHz Spootrum	Canabilities (con	tinuad\	
20 MHz Channel Width in 2.4 GHz 40 MHz Channel Width in 2.4 GHz	80 MHz Channel Widt 160 MHz Channel Wid	6 GHz Spectrum Capabilities (continued)  80 MHz Channel Width in 6 GHz  160 MHz Channel Width in 6 GHz  320 MHz channel width in 6 GHz		
5 GHz Spectrum Capabilities	Protected Manag	Protected Management Frames		
20 MHz Channel Width in 5 GHz 40 MHz Channel Width in 5 GHz 80 MHz Channel Width in 5 GHz	Spectrum & Reg	Spectrum & Regulatory		
160 MHz Channel Width in 5 GHz	802.11h			
6 GHz Spectrum Capabilities	WMM®			
20 MHz Channel Width in 6 GHz 40 MHz Channel Width in 6 GHz	WPA2™-Enterpr	ise 2018-04		



**Certification ID: WFA133221** 



Role: Access Point Page 3 of 4

### WPA2<sup>™</sup>-Enterprise 2018-04 (continued)

EAP methods

### WPA2™-Personal 2021-01

#### WPA3™-Enterprise 2022-12

EAP methods

#### WPA3™-Personal 2024-10

AKM 24

**Beacon Protection** 

SAE-Public Key

### Wi-Fi Agile Multiband™

Cellular Data aware

### Wi-Fi CERTIFIED 6® Release 2

A-MPDU with A-MSDU

Basic Trigger frame in HE MU PPDU

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

DL OFDMA

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

# Wi-Fi CERTIFIED 6® Release 2 (continued)

MCS 10-11 Tx

MU-BAR Trigger frame

MU-RTS Trigger frame

Operating mode subfield in A-Control field

Operating mode indication

Operating mode UL MU Rx

SU beamformer

SU-MIMO

TXOP RTS Threshold

**UL OFDMA** 

Wi-Fi 6E

Co-located BSS

Wi-Fi 6 Release 2 features

**UL MU-MIMO** 

**UL MU Control** 

**UL Extended Range** 

Target Wake Time information frames

**Broadcast Target Wake Time** 

Dynamic MU SMPS

M-BSSID control frames

#### Wi-Fi CERTIFIED 7™

A-MPDU with A-MSDU

**BSRP** Trigger frame

BSS critical update

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

Compressed Block Ack Rx (buffer size 512)

Compressed Block Ack Tx (buffer size 512)

DL MU-MIMO

DL OFDMA

Dynamic MU SMPS

EMLSR (Enhanced Multilink Single-Radio)



**Certification ID: WFA133221** 



Role: Access Point Page 4 of 4

# Wi-Fi CERTIFIED 7™ (continued)

EPCS (Emergency Preparedness Communications Services) priority access

LDPC Rx

LDPC Tx

Load Balancing in MLO

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MCS 12-13 Rx

MCS 12-13 Tx

Multi-link reconfiguration - AP removal

Multi-RU

MU-RTS Trigger frame

Operating mode indication

Operating mode indication for 320 MHz

Static puncturing

STR (Simultaneous Transmit and Receive)

SU-MIMO

Triggered uplink access optimization

UL MU-MIMO

**UL OFDMA** 

### Wi-Fi CERTIFIED™ a

#### Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

LDPC Tx

MCS 8-9 Rx

RTS with BW Signaling

Short Guard Interval

STBC

# Wi-Fi CERTIFIED™ ac (continued)

SU beamformer

### Wi-Fi CERTIFIED™ b

### Wi-Fi CERTIFIED™ g

### Wi-Fi CERTIFIED™ n

A-MPDU Tx

**OBSS** on Extension Channel

Short Guard Interval

STBC

# Wi-Fi Enhanced Open™ 2023-12