



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA133182

Product Info

Date of Certification October 31, 2024

Company Huawei Technologies Co., Ltd.

Product Name Wireless LAN Access Point

Product Model Variant AirEngine6776-X6ETH ver.2024

Model Number AirEngine6776-X6ETH

Category Routers

Sub-category Enterprise/Service Provider Access Point, Switch/Controller or Router

Summary of Certifications

CI ASSIFICAT	ION (CERTIFICA	TION

Connectivity 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities6 GHz Spectrum Capabilities

Wi-Fi CERTIFIED 6®
Wi-Fi CERTIFIED 7™
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n

Optimization WMM®

Wi-Fi Agile Multiband™

Security Protected Management Frames

WPA2[™]-Enterprise 2018-04 WPA2[™]-Personal 2021-01 WPA3[™]-Enterprise 2022-12 WPA3[™]-Personal 2023-12



Certification ID: WFA133182



Role: Access Point	Page 2 of 4	
Vi-Fi Components		
Wi-Fi Component Operating System	RF Architecture	
HongMeng	Bands Supported Transmit (Tx) Receive (Rx	
Wi-Fi Component Firmware	2.4 GHz 2 2	
Ver.A	5 GHz 4 4	
	6 GHz 2 2	
Certifications		
2.4 GHz Spectrum Capabilities	WPA2™-Enterprise 2018-04 (continued)	
20 MHz Channel Width in 2.4 GHz	EAP methods	
40 MHz Channel Width in 2.4 GHz		
5 GHz Spectrum Capabilities	WPA2™-Personal 2021-01	
20 MHz Channel Width in 5 GHz	WPA3™-Enterprise 2022-12	
40 MHz Channel Width in 5 GHz	EAP methods	
80 MHz Channel Width in 5 GHz 160 MHz Channel Width in 5 GHz	192-bit security	
	WPA3™-Personal 2023-12	
6 GHz Spectrum Capabilities	AVM 24	
20 MHz Channel Width in 6 GHz	AKM 24 Beacon Protection	
40 MHz Channel Width in 6 GHz		
80 MHz Channel Width in 6 GHz	Wi-Fi Agile Multiband™	
Protected Management Frames	Wi-Fi CERTIFIED 6®	
WMM®	4 antenna support	
	A-MPDU with A-MSDU	



Certification ID: WFA133182



Role: Access Point Page 3 of 4

Wi-Fi CERTIFIED 6® (continued)

BSRP Trigger frame

Co-located BSS

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

DL OFDMA

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

Operating mode indication

SU-MIMO

UL OFDMA

Wi-Fi 6E

Wi-Fi CERTIFIED 7™

A-MPDU with A-MSDU

BSRP Trigger frame

BSS critical update

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

Compressed Block Ack Rx (buffer size 512)

Compressed Block Ack Tx (buffer size 512)

DL MU-MIMO

DL OFDMA

Dynamic MU SMPS

EMLSR (Enhanced Multilink Single-Radio)

LDPC Rx

LDPC Tx

MCS 8-9 Rx

Wi-Fi CERTIFIED 7™ (continued)

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

Multi-RU

Operating mode indication

Static puncturing

STR (Simultaneous Transmit and Receive)

SU-MIMO

Triggered uplink access optimization

UL MU-MIMO

UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

LDPC Tx

MCS 8-9 Rx

RTS with BW Signaling

Short Guard Interval

STBC

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx

HT Duplicate Mode

OBSS on Extension Channel





Certification ID: WFA133182