Wi-Fi CERTIFIED® Certificate

This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org

Certification ID: WFA133496

Product Info

Date of Certification	November 12, 2024
Company	Chongqing SeekWave Technology Co. Ltd
Product Name	EA6521QF – Wi-Fi 6 and Bluetooth Combo
Product Model Variant	EA6521QF
Model Number	EA6521QF
Category	Other
Sub-category	Chipset

Summary of Certifications

CLASSIFICATION	CERTIFICATION
Network management	WMM® Wi-Fi Agile Multiband™
Security	Protected Management Frames WPA2™-Enterprise 2018-04 WPA2™-Personal 2021-01 WPA3™-Enterprise 2020-02 WPA3™-Personal 2020-12
Wi-Fi (MAC/PHY)	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Spectrum & Regulatory Wi-Fi CERTIFIED 6® Release 2 Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n

Wi-Fi CERTIFIED® Certificate

Certification ID: WFA133496

Wi-Fi Components

Wi-Fi Component Operating System
RTOS

Wi-Fi Component Firmware
Ver0.9.0

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	1	1
5 GHz	1	1

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz
40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz

Protected Management Frames

Spectrum & Regulatory

802.11h

WMM®

WPA2™-Enterprise 2018-04

EAP methods
    EAP TLS
    EAP TTLS

WPA2™-Enterprise 2018-04 (continued)

    PEAPv0
    PEAPv1

WPA2™-Personal 2021-01

WPA3™-Enterprise 2020-02

EAP methods
    EAP TLS
    EAP TTLS
    PEAPv0
    PEAPv1
Server Certificate Validation

WPA3™-Personal 2020-12

Wi-Fi Agile Multiband™

ANQP
ANQP-based Neighbor report
Beacon Report Measurement Active Mode
Beacon Report Measurement Passive Mode
BTM Query

Wi-Fi Agile Multiband™ (continued)

Fast Transition OTA on WPA2-Personal

Fast Transition OTA on WPA2-Enterprise

Wi-Fi CERTIFIED 6® Release 2

A-MPDU with A-MSDU

Beamforming sounding

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

LDPC Tx

LDPC Rx

Individual Target Wake Time

MCS 10-11 Rx

MCS 10-11 Tx

MCS 8-9 Rx

MCS 8-9 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

MU-RTS Trigger frame

M-BSSID

Operating mode control field

Operating mode subfield in A-Control field

Operating mode indication

SU beamformee

SU-MIMO

UL OFDMA

Wi-Fi 6 Release 2 features

- UL MU-MIMO
- UL Extended Range
- Target Wake Time information frames
- Broadcast Target Wake Time
- Extended sleep time
- M-BSSID control frames

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

Extended 5 GHz Channel Support

RTS with BW Signaling

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

MCS 8-9 Rx

Short Guard Interval

STBC

LDPC Tx

SU beamformee

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx

OBSS on Extension Channel

Short Guard Interval

STBC