



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA133707

Product Info

Date of Certification December 3, 2024

Company Allied Telesis Holdings K.K.

Product Name AT-TQm3403

Product Model Variant New Product Model

Model Number AT-TQm3403

Category Routers

Sub-category Enterprise/Service Provider Access Point, Switch/Controller or Router

Summary of Certifications

CLASSIFICATION CERTIFICATION

Access Passpoint® Release 3

Connectivity 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities 6 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Release 2

Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n

Wi-Fi Enhanced Open™ 2023-12

Optimization WMM®

WMM®-Power Save Wi-Fi Agile Multiband™

Security Protected Management Frames

WPA2[™]-Enterprise 2018-04 WPA2[™]-Personal 2021-01 WPA3[™]-Enterprise 2022-12 WPA3[™]-Personal 2024-10





Certification ID: WFA133707

Summary	of Cert	ifications	(cont	inued)
- Cullilliai		illoutions	,00110	iiiaca,

Page 2 of 5

CLASSIFICATION

CERTIFICATION

Spectrum & Regulatory

Spectrum & Regulatory

Features



Certification ID: WFA133707



Role: Access Point	Page 3 of 5

Wi-Fi Components

Wi-Fi Component Operating System

Linux

Wi-Fi Component Firmware

WLAN.HK.2.9-02509-QCAHKSWPL SILICONZ-1 v1

RF Architecture

Bands Supported Transmit (Tx) Receive (Rx)

2.4 GHz 2 2

Wi-Fi Component Operating System

Linux

Wi-Fi Component Firmware

WLAN.HK.2.9-02509-QCAHKSWPL_SILICONZ-1 v1

RF Architecture

Bands Supported Transmit (Tx) Receive (Rx)

5 GHz 2 2

Wi-Fi Component Operating System

Linux

Wi-Fi Component Firmware

WLAN.HK.2.9-02509-QCAHKSWPL_SILICONZ-1 v1

RF Architecture

Bands Supported Transmit (Tx) Receive (Rx)

6 GHz 2 2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz 40 MHz Channel Width in 2.4 GHz

6 GHz Spectrum Capabilities (continued)

20 MHz Channel Width in 6 GHz 40 MHz Channel Width in 6 GHz 80 MHz Channel Width in 6 GHz

160 MHz Channel Width in 6 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz 40 MHz Channel Width in 5 GHz 80 MHz Channel Width in 5 GHz 160 MHz Channel Width in 5 GHz

Passpoint® Release 3

Roaming Consortium Selection Terms and Conditions Venue Information

6 GHz Spectrum Capabilities

Protected Management Frames



Certification ID: WFA133707



Role: Access Point Page 4 of 5

Spectrum & Regulatory

802.11d

802.11h

WMM®

WMM®-Power Save

Unschedule auto PS

WPA2™-Enterprise 2018-04

EAP methods

WPA2™-Personal 2021-01

WPA3™-Enterprise 2022-12

EAP methods

192-bit security

Fast Transition OTA on WPA3-Enterprise

WPA3™-Personal 2024-10

Fast Transition OTA on WPA3-Personal

Fast Transition OTA on WPA3-Personal transition mode

Wi-Fi Agile Multiband™

Automatically populate BSS Transition candidate list

Cellular Data aware

Fast Transition OTA on WPA2-Enterprise

Fast Transition OTA on WPA2-Personal

Wi-Fi CERTIFIED 6® Release 2

A-MPDU with A-MSDU

Basic Trigger frame in HE MU PPDU

BSRP Trigger frame

Co-located BSS

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL OFDMA

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

MU-RTS Trigger frame

M-BSSID

Operating mode indication

SU beamformer

SU-MIMO

TXOP RTS Threshold

UL OFDMA

Wi-Fi 6E

Wi-Fi 6 Release 2 features

UL Extended Range

Target Wake Time information frames

Extended sleep

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU

Extended 5 GHz Channel Support





Certification ID: WFA133707

Role: Access Point Page 5 of 5 Wi-Fi CERTIFIED™ ac (continued) LDPC Rx LDPC Tx MCS 8-9 Rx RTS with BW Signaling Short Guard Interval **STBC** SU beamformer Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n A-MPDU Tx **OBSS** on Extension Channel Short Guard Interval STBC Wi-Fi Enhanced Open™ 2023-12