Wi-Fi CERTIFIED™ Certificate

This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA133707

Product Info

Date of Certification	December 3, 2024
Company	Allied Telesis Holdings K.K.
Product Name	AT-TQm3403
Product Model Variant	New Product Model
Model Number	AT-TQm3403
Category	Routers
Sub-category	Enterprise/Service Provider Access Point, Switch/Controller or Router

Summary of Certifications

CLASSIFICATION	CERTIFICATION
Access	Passpoint® Release 3
Network management	WMM® WMM®-Power Save Wi-Fi Agile Multiband™
Security	Protected Management Frames WPA2™-Enterprise 2018-04 WPA2™-Personal 2021-01 WPA3™-Enterprise 2022-12 WPA3™-Personal 2024-10 Wi-Fi Enhanced Open™ 2023-12
Wi-Fi (MAC/PHY)	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities 6 GHz Spectrum Capabilities Spectrum & Regulatory Wi-Fi CERTIFIED 6® Release 2 Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n

Wi-Fi Components

Wi-Fi Component Operating System

Linux

Wi-Fi Component Firmware

WLAN.HK.2.9-02509-QCAHKSWPL_SILICONZ-1 v1

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2

Wi-Fi Component Operating System

Linux

Wi-Fi Component Firmware

WLAN.HK.2.9-02509-QCAHKSWPL_SILICONZ-1 v1

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
5 GHz	2	2

Wi-Fi Component Operating System

Linux

Wi-Fi Component Firmware

WLAN.HK.2.9-02509-QCAHKSWPL_SILICONZ-1 v1

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
6 GHz	2	2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz
40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz
160 MHz Channel Width in 5 GHz

6 GHz Spectrum Capabilities

6 GHz Spectrum Capabilities (continued)

20 MHz Channel Width in 6 GHz
40 MHz Channel Width in 6 GHz
80 MHz Channel Width in 6 GHz
160 MHz Channel Width in 6 GHz

Passpoint® Release 3

Roaming Consortium Selection
Terms and Conditions
Venue Information

Protected Management Frames

Spectrum & Regulatory

802.11d
802.11h

WMM®

WMM®-Power Save

Unschedule auto PS

WPA2™-Enterprise 2018-04

EAP methods

WPA2™-Personal 2021-01

WPA3™-Enterprise 2022-12

EAP methods
192-bit security
Fast Transition OTA on WPA3-Enterprise

WPA3™-Personal 2024-10

Fast Transition OTA on WPA3-Personal
Fast Transition OTA on WPA3-Personal transition mode

Wi-Fi Agile Multiband™

Automatically populate BSS Transition candidate list
Cellular Data aware
Fast Transition OTA on WPA2-Enterprise
Fast Transition OTA on WPA2-Personal

Wi-Fi CERTIFIED 6® Release 2

A-MPDU with A-MSDU
Basic Trigger frame in HE MU PPDU
BSRP Trigger frame
Compressed Block Ack Rx (buffer size 256)
Compressed Block Ack Tx (buffer size 256)
DL OFDMA
Individual Target Wake Time
LDPC Rx
LDPC Tx
MCS 8-9 Rx
MCS 8-9 Tx
MCS 10-11 Rx
MCS 10-11 Tx
MU EDCA Parameter Set element
MU-BAR Trigger frame
MU-RTS Trigger frame
M-BSSID
Operating mode subfield in A-Control field
Operating mode indication
Operating mode UL MU Rx
SU beamformer
SU-MIMO
TXOP RTS Threshold
UL OFDMA
Wi-Fi 6E
    Co-located BSS
Wi-Fi 6 Release 2 features
    UL Extended Range
    Target Wake Time information frames
    Extended sleep

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

Wi-Fi CERTIFIED™ ac (continued)

A-MPDU with A-MSDU

Extended 5 GHz Channel Support

LDPC Rx

LDPC Tx

MCS 8-9 Rx

RTS with BW Signaling

Short Guard Interval

STBC

SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx

OBSS on Extension Channel

Short Guard Interval

STBC

Wi-Fi Enhanced Open™ 2023-12