



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA133795

Product Info

Date of Certification March 10, 2025

Company Cisco Systems

Product Name Cisco Catalyst 9800-L Wireless Controller and Cisco CW9172H AP

Product Model Variant Cisco IOS XE: 17.17

Model Number C9800-L and CW9172H

Category Routers

Sub-category Enterprise/Service Provider Access Point, Switch/Controller or Router

Summary of Certifications

CLASSIFICATION CERTIFICATION

Connectivity 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities6 GHz Spectrum CapabilitiesWi-Fi CERTIFIED 6® Release 2

Wi-Fi CERTIFIED 7™
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n

Wi-Fi Enhanced Open™ 2023-12

Optimization WMM®

WMM®-Power Save Wi-Fi Agile Multiband™

Security Protected Management Frames

WPA2[™]-Enterprise 2018-04 WPA2[™]-Personal 2021-01 WPA3[™]-Enterprise 2022-12 WPA3[™]-Personal 2024-10



Certification ID: WFA133795



Summary of Certifications (continued)

Page 2 of 5

CLASSIFICATION

CERTIFICATION

Spectrum & Regulatory

Spectrum & Regulatory

Features



Certification ID: WFA133795



Polo: Access Point	Page 2 of 5
Role: Access Point	Page 3 of 5

Wi-Fi Components

Wi-Fi Component Operating System

Linux, Version: 17.17

Wi-Fi Component Firmware

17.17

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2
6 GHz	2	2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz

40 MHz Channel Width in 5 GHz

80 MHz Channel Width in 5 GHz

160 MHz Channel Width in 5 GHz

6 GHz Spectrum Capabilities

Standard power operation

20 MHz Channel Width in 6 GHz

40 MHz Channel Width in 6 GHz

80 MHz Channel Width in 6 GHz

160 MHz Channel Width in 6 GHz

320 MHz channel width in 6 GHz

Protected Management Frames

Spectrum & Regulatory

Spectrum & Regulatory (continued)

802.11d

802.11h

WMM®

WMM®-Power Save

Legacy Power Save

Unschedule auto PS

WPA2™-Enterprise 2018-04

EAP methods

WPA2™-Personal 2021-01

WPA3™-Enterprise 2022-12

EAP methods

192-bit security

Fast Transition OTA on WPA3-Enterprise



Certification ID: WFA133795



Role: Access Point Page 4 of 5

WPA3™-Enterprise 2022-12 (continued)

Fast Transition OTA on WPA3-Enterprise transition mode Fast Transition OTDS on WPA3-Enterprise

WPA3™-Personal 2024-10

AKM 24

AKM 25

Fast Transition OTA on WPA3-Personal

Fast Transition OTA on WPA3-Personal transition mode

Fast Transition OTDS on WPA3-Personal

Beacon Protection

Wi-Fi Agile Multiband™

Automatically populate BSS Transition candidate list

Fast Transition OTA on WPA2-Enterprise

Fast Transition OTA on WPA2-Personal

Wi-Fi CERTIFIED 6® Release 2

A-MPDU with A-MSDU

Beamforming sounding

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL OFDMA

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

Wi-Fi CERTIFIED 6® Release 2 (continued)

MU-BAR Trigger frame

MU-RTS Trigger frame

Operating mode subfield in A-Control field

Operating mode indication

Operating mode UL MU Rx

SU beamformer

SU-MIMO

UL OFDMA

Wi-Fi 6E

Co-located BSS

Multiple M-BSSID

Wi-Fi 6 Release 2 features

UL MU Control

UL Extended Range

Target Wake Time information frames

Extended sleep

Dynamic MU SMPS

Wi-Fi CERTIFIED 7™

A-MPDU with A-MSDU

Beamforming sounding

BSRP Trigger frame

BSS critical update

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

Compressed Block Ack Rx (buffer size 512)

Compressed Block Ack Tx (buffer size 512)

DL OFDMA

Dynamic MU SMPS

EMLSR (Enhanced Multilink Single-Radio)

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx



Certification ID: WFA133795



Role: Access Point Page 5 of 5

Wi-Fi CERTIFIED 7™ (continued)

MCS 10-11 Rx

MCS 10-11 Tx

MCS 12-13 Tx

Multi-RU

MU-RTS Trigger frame

Operating mode indication

Operating mode indication for 320 MHz

Static puncturing

STR (Simultaneous Transmit and Receive)

SU-MIMC

Triggered uplink access optimization

UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU

Extended 5 GHz Channel Support

LDPC Rx

LDPC Tx

MCS 8-9 Rx

RTS with BW Signaling

Short Guard Interval

STBC

SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx

Wi-Fi CERTIFIED™ n (continued)

OBSS on Extension Channel

Short Guard Interval

STBC

Wi-Fi Enhanced Open™ 2023-12