



Wi-Fi CERTIFIED™ Certificate



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA128184

Product Info

Date of Certification	January 9, 2025
Company	Qualcomm
Product Name	Qualcomm Networking Pro Tri-Band Wi-Fi 7 Platform
Product Model Variant	Add proximity detection
Model Number	IPQ9574
Category	Other
Sub-category	Reference Design

Summary of Certifications

CLASSIFICATION	CERTIFICATION
Applications & Services	Proximity Detection
Connectivity	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities 6 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Release 2 Wi-Fi CERTIFIED 7™ Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n Wi-Fi Enhanced Open™ 2023-12
Optimization	WMM® Wi-Fi Agile Multiband™
Security	Protected Management Frames WPA2™-Enterprise 2018-04 WPA2™-Personal 2021-01 WPA3™-Enterprise 2022-12 WPA3™-Personal 2024-10



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA128184



Summary of Certifications (continued)

Page 2 of 5

CLASSIFICATION

CERTIFICATION

Spectrum & Regulatory
Features

Spectrum & Regulatory



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA128184



Role: Access Point

Page 3 of 5

Wi-Fi Components

Wi-Fi Component Operating System

Linux

Wi-Fi Component Firmware

IPQ9574.WFA.12.5-00008-P-1

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	4	4
5 GHz	4	4
6 GHz	4	4

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz
40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz
160 MHz Channel Width in 5 GHz

6 GHz Spectrum Capabilities

20 MHz Channel Width in 6 GHz
40 MHz Channel Width in 6 GHz
80 MHz Channel Width in 6 GHz
160 MHz Channel Width in 6 GHz
320 MHz channel width in 6 GHz

Protected Management Frames

Proximity Detection

Proximity Detection (continued)

Proximity Detection role
Initiating STA for Proximity Detection
Responding STA for Proximity Detection

Spectrum & Regulatory

802.11d
802.11h

WMM®

WPA2™-Enterprise 2018-04

EAP methods

WPA2™-Personal 2021-01

WPA3™-Enterprise 2022-12

EAP methods
192-bit security



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA128184



Role: Access Point

Page 4 of 5

WPA3™-Enterprise 2022-12 (continued)

Fast Transition OTA on WPA3-Enterprise
Fast Transition OTA on WPA3-Enterprise transition mode
Fast Transition OTDS on WPA3-Enterprise

WPA3™-Personal 2024-10

AKM 24
AKM 25
WPA3-Personal compatibility mode
Fast Transition OTA on WPA3-Personal
Fast Transition OTA on WPA3-Personal transition mode
Fast Transition OTDS on WPA3-Personal
Beacon Protection
SAE-Public Key
Operating Channel Validation

Wi-Fi Agile Multiband™

Automatically populate BSS Transition candidate list
Cellular Data aware
Fast Transition OTA on WPA2-Enterprise
Fast Transition OTA on WPA2-Personal

Wi-Fi CERTIFIED 6® Release 2

4 antenna support
A-MPDU with A-MSDU
Basic Trigger frame in HE MU PPDU
Beamforming sounding
BSRP Trigger frame
Co-located BSS
Compressed Block Ack Rx (buffer size 256)
Compressed Block Ack Tx (buffer size 256)
DL MU-MIMO

Wi-Fi CERTIFIED 6® Release 2 (continued)

DL OFDMA
Individual Target Wake Time
LDPC Rx
LDPC Tx
MCS 8-9 Rx
MCS 8-9 Tx
MCS 10-11 Rx
MCS 10-11 Tx
MU EDCA Parameter Set element
MU-BAR Trigger frame
MU-RTS Trigger frame
M-BSSID
Operating mode indication
SU beamformer
SU-MIMO
TXOP RTS Threshold
UL OFDMA
Wi-Fi 6E
Multiple M-BSSID
Wi-Fi 6 Release 2 features
UL MU-MIMO
UL MU Control
UL Extended Range
Target Wake Time information frames
Broadcast Target Wake Time
Extended sleep
Dynamic MU SMPS
M-BSSID control frames

Wi-Fi CERTIFIED 7™

Advertised TID-to-link mapping
A-MPDU with A-MSDU
Beamforming sounding
BSRP Trigger frame



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA128184



Role: Access Point

Page 5 of 5

Wi-Fi CERTIFIED 7™ (continued)

BSS critical update
Compressed Block Ack Rx (buffer size 256)
Compressed Block Ack Tx (buffer size 256)
Compressed Block Ack Rx (buffer size 512)
Compressed Block Ack Tx (buffer size 512)
DL MU-MIMO
DL OFDMA
Dynamic MU SMPS
EMLSR (Enhanced Multilink Single-Radio)
EPCS (Emergency Preparedness Communications Services) priority access
LDPC Rx
LDPC Tx
Load Balancing in MLO
MCS 8-9 Rx
MCS 8-9 Tx
MCS 10-11 Rx
MCS 10-11 Tx
MCS 12-13 Rx
MCS 12-13 Tx
Multi-link reconfiguration – AP removal
Multi-link reconfiguration – AP restart
Multi-RU
MU-RTS Trigger frame
Operating mode indication
 Operating mode indication for 320 MHz
Static puncturing
STR (Simultaneous Transmit and Receive)
SU-MIMO
Triggered uplink access optimization
UL MU-MIMO
UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

Wi-Fi CERTIFIED™ ac (continued)

A-MPDU with A-MSDU
DL MU-MIMO
Extended 5 GHz Channel Support
LDPC Rx
LDPC Tx
MCS 8 Rx
MCS 8-9 Rx
RTS with BW Signaling
Short Guard Interval
STBC
SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx
HT Duplicate Mode
OBSS on Extension Channel
RIFS
Short Guard Interval
STBC

Wi-Fi Enhanced Open™ 2023-12