



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA128184

Product Info

Date of Certification January 9, 2025

Company Qualcomm

Product Name Qualcomm Networking Pro Tri-Band Wi-Fi 7 Platform

Product Model Variant Add proximity detection

Model Number IPQ9574

Category Other

Sub-category Reference Design

Summary of Certifications

CLASSIFICATION CERTIFICATION

Applications & Services Proximity Detection

Connectivity 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities6 GHz Spectrum CapabilitiesWi-Fi CERTIFIED 6® Release 2

Wi-Fi CERTIFIED 7™
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n

Wi-Fi Enhanced Open™ 2023-12

Optimization WMM®

Wi-Fi Agile Multiband™

Security Protected Management Frames

WPA2[™]-Enterprise 2018-04 WPA2[™]-Personal 2021-01 WPA3[™]-Enterprise 2022-12 WPA3[™]-Personal 2024-10



Certification ID: WFA128184



Summary of Certifications (continued)

Page 2 of 5

CLASSIFICATION

CERTIFICATION

Spectrum & Regulatory

Spectrum & Regulatory

Features



Certification ID: WFA128184



Role: Access Point		Page 3 of 5		
Wi-Fi Components				
Wi-Fi Component Operating System	RF Architecture			
Linux	Bands Supported	Transmit (Tx)	Receive (Rx)	
Wi-Fi Component Firmware IPQ9574.WFA.12.5-00008-P-1	2.4 GHz	4	4	
	5 GHz	4	4	
	6 GHz	4	4	
Certifications				
2.4 GHz Spectrum Capabilities	Proximity Detection (continued)			
20 MHz Channel Width in 2.4 GHz	Proximity Detection rol	Proximity Detection role		
40 MHz Channel Width in 2.4 GHz	Initiating STA for Proximity Detection Responding STA for Proximity Detection			
F GHz Spectrum Capabilities		,		
5 GHz Spectrum Capabilities				

6 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz 40 MHz Channel Width in 5 GHz

80 MHz Channel Width in 5 GHz

160 MHz Channel Width in 5 GHz

20 MHz Channel Width in 6 GHz 40 MHz Channel Width in 6 GHz 80 MHz Channel Width in 6 GHz 160 MHz Channel Width in 6 GHz 320 MHz channel width in 6 GHz

Protected Management Frames

Proximity Detection

802.11d

Spectrum & Regulatory

802.11h

WMM®

WPA2™-Enterprise 2018-04

EAP methods

WPA2™-Personal 2021-01

WPA3™-Enterprise 2022-12

EAP methods 192-bit security



Certification ID: WFA128184



Role: Access Point Page 4 of 5

WPA3™-Enterprise 2022-12 (continued)

Fast Transition OTA on WPA3-Enterprise

Fast Transition OTA on WPA3-Enterprise transition mode

Fast Transition OTDS on WPA3-Enterprise

WPA3™-Personal 2024-10

AKM 24

AKM 25

WPA3-Personal compatibility mode

Fast Transition OTA on WPA3-Personal

Fast Transition OTA on WPA3-Personal transition mode

Fast Transition OTDS on WPA3-Personal

Beacon Protection

SAE-Public Key

Operating Channel Validation

Wi-Fi Agile Multiband™

Automatically populate BSS Transition candidate list

Cellular Data aware

Fast Transition OTA on WPA2-Enterprise

Fast Transition OTA on WPA2-Personal

Wi-Fi CERTIFIED 6® Release 2

4 antenna support

A-MPDU with A-MSDU

Basic Trigger frame in HE MU PPDU

Beamforming sounding

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

DL OFDMA

Wi-Fi CERTIFIED 6® Release 2 (continued)

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

MU-RTS Trigger frame

M-BSSID

Operating mode subfield in A-Control field

Operating mode indication

Operating mode UL MU Rx

SU beamformer

SU-MIMO

TXOP RTS Threshold

UL OFDMA

Wi-Fi 6E

Co-located BSS

Multiple M-BSSID

Wi-Fi 6 Release 2 features

UL MU-MIMO

UL MU Control

UL Extended Range

Target Wake Time information frames

Broadcast Target Wake Time

Extended sleep

Dynamic MU SMPS

M-BSSID control frames

Wi-Fi CERTIFIED 7™

Advertised TID-to-link mapping

A-MPDU with A-MSDU



Certification ID: WFA128184



Role: Access Point Page 5 of 5

Wi-Fi CERTIFIED 7™ (continued)

Beamforming sounding

BSRP Trigger frame

BSS critical update

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

Compressed Block Ack Rx (buffer size 512)

Compressed Block Ack Tx (buffer size 512)

DL MU-MIMO

DL OFDMA

Dynamic MU SMPS

EMLSR (Enhanced Multilink Single-Radio)

EPCS (Emergency Preparedness Communications Services)

priority access

LDPC Rx

LDPC Tx

Load Balancing in MLO

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MCS 12-13 Rx

MCS 12-13 Tx

 $\hbox{Multi-link reconfiguration}-\hbox{AP removal}$

Multi-link reconfiguration - AP restart

Multi-RU

MU-RTS Trigger frame

Operating mode indication

Operating mode indication for 320 MHz

Static puncturing

STR (Simultaneous Transmit and Receive)

SU-MIMO

Triggered uplink access optimization

UL MU-MIMO

UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU

DL MU-MIMO

Extended 5 GHz Channel Support

LDPC Rx

LDPC Tx

MCS 8 Rx

MCS 8-9 Rx

RTS with BW Signaling

Short Guard Interval

STBC

SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx

HT Duplicate Mode

OBSS on Extension Channel

RIFS

Short Guard Interval

STBC

Wi-Fi Enhanced Open™ 2023-12