



# Wi-Fi CERTIFIED™ Certificate



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: [www.wi-fi.org/certification/programs](http://www.wi-fi.org/certification/programs)

## Certification ID: WFA128184

### Product Info

<b>Date of Certification</b>	January 9, 2025
<b>Company</b>	Qualcomm
<b>Product Name</b>	Qualcomm Networking Pro Tri-Band Wi-Fi 7 Platform
<b>Product Model Variant</b>	Add proximity detection
<b>Model Number</b>	IPQ9574
<b>Category</b>	Other
<b>Sub-category</b>	Reference Design

### Summary of Certifications

CLASSIFICATION	CERTIFICATION
<b>Applications &amp; Services</b>	Proximity Detection
<b>Connectivity</b>	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities 6 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Release 2 Wi-Fi CERTIFIED 7™ Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n Wi-Fi Enhanced Open™ 2023-12
<b>Optimization</b>	WMM® Wi-Fi Agile Multiband™
<b>Security</b>	Protected Management Frames WPA2™-Enterprise 2018-04 WPA2™-Personal 2021-01 WPA3™-Enterprise 2022-12 WPA3™-Personal 2024-10



# Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA128184



## Summary of Certifications (continued)

Page 2 of 5

### CLASSIFICATION

### CERTIFICATION

Spectrum & Regulatory  
Features

Spectrum & Regulatory



# Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA128184



Role: Access Point

Page 3 of 5

## Wi-Fi Components

### Wi-Fi Component Operating System

Linux

### Wi-Fi Component Firmware

IPQ9574.WFA.12.5-00008-P-1

### RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	4	4
5 GHz	4	4
6 GHz	4	4

## Certifications

### 2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz  
40 MHz Channel Width in 2.4 GHz

### 5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz  
40 MHz Channel Width in 5 GHz  
80 MHz Channel Width in 5 GHz  
160 MHz Channel Width in 5 GHz

### 6 GHz Spectrum Capabilities

20 MHz Channel Width in 6 GHz  
40 MHz Channel Width in 6 GHz  
80 MHz Channel Width in 6 GHz  
160 MHz Channel Width in 6 GHz  
320 MHz channel width in 6 GHz

### Protected Management Frames

### Proximity Detection

### Proximity Detection (continued)

Proximity Detection role  
Initiating STA for Proximity Detection  
Responding STA for Proximity Detection

### Spectrum & Regulatory

802.11d  
802.11h

### WMM®

### WPA2™-Enterprise 2018-04

EAP methods

### WPA2™-Personal 2021-01

### WPA3™-Enterprise 2022-12

EAP methods  
192-bit security



# Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA128184



Role: Access Point

Page 4 of 5

## WPA3™-Enterprise 2022-12 (continued)

Fast Transition OTA on WPA3-Enterprise  
Fast Transition OTA on WPA3-Enterprise transition mode  
Fast Transition OTDS on WPA3-Enterprise

## WPA3™-Personal 2024-10

AKM 24  
AKM 25  
WPA3-Personal compatibility mode  
Fast Transition OTA on WPA3-Personal  
Fast Transition OTA on WPA3-Personal transition mode  
Fast Transition OTDS on WPA3-Personal  
Beacon Protection  
SAE-Public Key  
Operating Channel Validation

## Wi-Fi Agile Multiband™

Automatically populate BSS Transition candidate list  
Cellular Data aware  
Fast Transition OTA on WPA2-Enterprise  
Fast Transition OTA on WPA2-Personal

## Wi-Fi CERTIFIED 6® Release 2

4 antenna support  
A-MPDU with A-MSDU  
Basic Trigger frame in HE MU PPDU  
Beamforming sounding  
BSRP Trigger frame  
Compressed Block Ack Rx (buffer size 256)  
Compressed Block Ack Tx (buffer size 256)  
DL MU-MIMO  
DL OFDMA

## Wi-Fi CERTIFIED 6® Release 2 (continued)

Individual Target Wake Time  
LDPC Rx  
LDPC Tx  
MCS 8-9 Rx  
MCS 8-9 Tx  
MCS 10-11 Rx  
MCS 10-11 Tx  
MU EDCA Parameter Set element  
MU-BAR Trigger frame  
MU-RTS Trigger frame  
M-BSSID  
Operating mode indication  
SU beamformer  
SU-MIMO  
TXOP RTS Threshold  
UL OFDMA  
Wi-Fi 6E  
Co-located BSS  
Multiple M-BSSID  
Wi-Fi 6 Release 2 features  
UL MU-MIMO  
UL MU Control  
UL Extended Range  
Target Wake Time information frames  
Broadcast Target Wake Time  
Extended sleep  
Dynamic MU SMPS  
M-BSSID control frames

## Wi-Fi CERTIFIED 7™

Advertised TID-to-link mapping  
A-MPDU with A-MSDU  
Beamforming sounding  
BSRP Trigger frame



# Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA128184



Role: Access Point

Page 5 of 5

## Wi-Fi CERTIFIED 7™ (continued)

BSS critical update  
Compressed Block Ack Rx (buffer size 256)  
Compressed Block Ack Tx (buffer size 256)  
Compressed Block Ack Rx (buffer size 512)  
Compressed Block Ack Tx (buffer size 512)  
DL MU-MIMO  
DL OFDMA  
Dynamic MU SMPS  
EMLSR (Enhanced Multilink Single-Radio)  
EPCS (Emergency Preparedness Communications Services) priority access  
LDPC Rx  
LDPC Tx  
Load Balancing in MLO  
MCS 8-9 Rx  
MCS 8-9 Tx  
MCS 10-11 Rx  
MCS 10-11 Tx  
MCS 12-13 Rx  
MCS 12-13 Tx  
Multi-link reconfiguration – AP removal  
Multi-link reconfiguration – AP restart  
Multi-RU  
MU-RTS Trigger frame  
Operating mode indication  
    Operating mode indication for 320 MHz  
Static puncturing  
STR (Simultaneous Transmit and Receive)  
SU-MIMO  
Triggered uplink access optimization  
UL MU-MIMO  
UL OFDMA

## Wi-Fi CERTIFIED™ a

## Wi-Fi CERTIFIED™ ac

## Wi-Fi CERTIFIED™ ac (continued)

A-MPDU with A-MSDU  
DL MU-MIMO  
Extended 5 GHz Channel Support  
LDPC Rx  
LDPC Tx  
MCS 8 Rx  
MCS 8-9 Rx  
RTS with BW Signaling  
Short Guard Interval  
STBC  
SU beamformer

## Wi-Fi CERTIFIED™ b

## Wi-Fi CERTIFIED™ g

## Wi-Fi CERTIFIED™ n

A-MPDU Tx  
HT Duplicate Mode  
OBSS on Extension Channel  
RIFS  
Short Guard Interval  
STBC

## Wi-Fi Enhanced Open™ 2023-12