

Wi-Fi CERTIFIED™ Certificate



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA134271

Product Info

Date of Certification January 22, 2025

Company Cisco Systems

Product Name Cisco Catalyst CW9800H1 Wireless Controller and Cisco CW9172I AP

Product Model Variant Cisco IOS XE: 17.17

Model Number CW9800H1 with CW9172I

Category Routers

Sub-category Enterprise/Service Provider Access Point, Switch/Controller or Router

Summary of Certifications

CLASSIFICATION CERTIFICATION

Network management WMM®

WMM®-Power Save Wi-Fi Agile Multiband™

Security Protected Management Frames

WPA2[™]-Enterprise 2018-04 WPA2[™]-Personal 2021-01 WPA3[™]-Enterprise 2022-12 WPA3[™]-Personal 2024-10 Wi-Fi Enhanced Open[™] 2023-12

Wi-Fi (MAC/PHY) 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities 6 GHz Spectrum Capabilities Spectrum & Regulatory

Wi-Fi CERTIFIED 6® Release 2

Wi-Fi CERTIFIED 7™
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n



Spectrum & Regulatory

Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA134271



Role: Access Point		P	Page 2 of 4	
Wi-Fi Components				
Wi-Fi Component Operating System	RF Architecture			
Linux, Version: 17.17	Bands Supported	Transmit (Tx)	Receive (Rx)	
Wi-Fi Component Firmware 17.17	2.4 GHz	2	2	
	5 GHz	2	2	
	6 GHz	2	2	
Certifications				
2.4 GHz Spectrum Capabilities	Spectrum & Regulatory (continued)			
20 MHz Channel Width in 2.4 GHz	802.11d			
	802.11h			
5 GHz Spectrum Capabilities	WMM®			
20 MHz Channel Width in 5 GHz	VVIVIIVI			
40 MHz Channel Width in 5 GHz	WMM®-Power Save			
80 MHz Channel Width in 5 GHz 160 MHz Channel Width in 5 GHz	Legacy Power Save			
	Unschedule auto PS			
6 GHz Spectrum Capabilities				
Standard power operation	WPA2™-Enterpris	se 2018-04		
20 MHz Channel Width in 6 GHz	EAP methods			
40 MHz Channel Width in 6 GHz				
80 MHz Channel Width in 6 GHz	WPA2™-Persona	I 2021 - 01		
160 MHz Channel Width in 6 GHz 320 MHz channel width in 6 GHz				
320 MHz channel wigth in 6 GHz	WPA3™-Enterprise 2022-12			
Protected Management Frames	EAP methods			
	192-bit security			

Fast Transition OTA on WPA3-Enterprise



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA134271



Role: Access Point Page 3 of 4

WPA3™-Enterprise 2022-12 (continued)

Fast Transition OTA on WPA3-Enterprise transition mode Fast Transition OTDS on WPA3-Enterprise

WPA3™-Personal 2024-10

AKM 24

AKM 25

Fast Transition OTA on WPA3-Personal

Fast Transition OTA on WPA3-Personal transition mode

Fast Transition OTDS on WPA3-Personal

Beacon Protection

Wi-Fi Agile Multiband™

Automatically populate BSS Transition candidate list

Fast Transition OTA on WPA2-Enterprise

Fast Transition OTA on WPA2-Personal

Wi-Fi CERTIFIED 6® Release 2

A-MPDU with A-MSDU

Beamforming sounding

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL OFDMA

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

Wi-Fi CERTIFIED 6® Release 2 (continued)

MU-BAR Trigger frame

MU-RTS Trigger frame

Operating mode subfield in A-Control field

Operating mode indication

Operating mode UL MU Rx

SU beamformer

SU-MIMO

UL OFDMA

Wi-Fi 6E

Co-located BSS

Multiple M-BSSID

Wi-Fi 6 Release 2 features

UL MU Control

UL Extended Range

Target Wake Time information frames

Extended sleep

Dynamic MU SMPS

Wi-Fi CERTIFIED 7™

A-MPDU with A-MSDU

Beamforming sounding

BSRP Trigger frame

BSS critical update

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

Compressed Block Ack Rx (buffer size 512)

Compressed Block Ack Tx (buffer size 512)

DL OFDMA

Dynamic MU SMPS

EMLSR (Enhanced Multilink Single-Radio)

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA134271



Role: Access Point Page 4 of 4

Wi-Fi CERTIFIED 7™ (continued)

MCS 10-11 Rx

MCS 10-11 Tx

MCS 12-13 Tx

Multi-RU

MU-RTS Trigger frame

Operating mode indication

Operating mode indication for 320 MHz

Static puncturing

STR (Simultaneous Transmit and Receive)

SU-MIMC

Triggered uplink access optimization

UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU

Extended 5 GHz Channel Support

LDPC Rx

LDPC Tx

MCS 8-9 Rx

RTS with BW Signaling

Short Guard Interval

STBC

SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx

Wi-Fi CERTIFIED™ n (continued)

OBSS on Extension Channel

Short Guard Interval

STBC

Wi-Fi Enhanced Open™ 2023-12