



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

#### **Certification ID: WFA131171**

#### **Product Info**

**Date of Certification** February 25, 2025

Company HAN Networks Co., Ltd.

Product Name HAN Access Point

Product Model Variant add MCS12-13

Model Number AP511

**Category** Routers

**Sub-category** Enterprise/Service Provider Access Point, Switch/Controller or Router

#### **Summary of Certifications**

CLASSIFICATION CERTIFICATION

Access Passpoint® Release 3

**Connectivity** 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities6 GHz Spectrum Capabilities

Wi-Fi CERTIFIED 6®
Wi-Fi CERTIFIED 7™
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ ac
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n

Wi-Fi Enhanced Open™ 2023-12

**Optimization** WMM®

WMM®-Power Save Wi-Fi Agile Multiband™

**Security** Protected Management Frames

WPA2<sup>™</sup>-Enterprise 2018-04 WPA2<sup>™</sup>-Personal 2021-01 WPA3<sup>™</sup>-Enterprise 2022-12 WPA3<sup>™</sup>-Personal 2023-12





**Certification ID: WFA131171** 

0	- f O	/4!	داء ۽ ۽ ۽ ۽
Summarv	of Certificati	ons (conti	nuea

Page 2 of 5

**CLASSIFICATION** 

**CERTIFICATION** 

Spectrum & Regulatory

Spectrum & Regulatory

**Features** 



**Certification ID: WFA131171** 



Role: Access Point	Page 3 of 5		
Wi-Fi Components			
Wi-Fi Component Operating System	RF Architecture		
linux 5.4	Bands Supported Transmit (Tx) Receive (Rx)		
Wi-Fi Component Firmware	2.4 GHz 2 2		
SPF 12.2	5 GHz 2 2		
	6 GHz 2 2		
Certifications			
2.4 GHz Spectrum Capabilities	Passpoint® Release 3 (continued)		
20 MHz Channel Width in 2.4 GHz	Terms and Conditions		
40 MHz Channel Width in 2.4 GHz	Venue Information		
5 GHz Spectrum Capabilities	Protected Management Frames		
O MHz Channel Width in 5 GHz Spectrum & Regulatory			
40 MHz Channel Width in 5 GHz	000 444		
80 MHz Channel Width in 5 GHz 160 MHz Channel Width in 5 GHz	802.11d 802.11h		
6 GHz Spectrum Capabilities	WMM®		
20 MHz Channel Width in 6 GHz	WMM®-Power Save		
40 MHz Channel Width in 6 GHz			
80 MHz Channel Width in 6 GHz  160 MHz Channel Width in 6 GHz	WPA2™-Enterprise 2018-04		
320 MHz channel width in 6 GHz	EAP methods		
Passpoint® Release 3	WPA2™-Personal 2021-01		
Roaming Consortium Selection	WPA3™-Enterprise 2022-12		



**Certification ID: WFA131171** 



Page 4 of 5

Role: Access Point

WPA3™-Enterprise 2022-12 (continued)

EAP methods 192-bit security

WPA3™-Personal 2023-12

AKM 24

**Beacon Protection** 

Wi-Fi Agile Multiband™

Automatically populate BSS Transition candidate list

Cellular Data aware

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU

Basic Trigger frame in HE MU PPDU

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL OFDMA

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

MU-RTS Trigger frame

M-BSSID

Operating mode subfield in A-Control field

Operating mode indication

Wi-Fi CERTIFIED 6® (continued)

Operating mode UL MU Rx

SU beamformer

SU-MIMO

TXOP RTS Threshold

**UL OFDMA** 

Wi-Fi 6E

Co-located BSS

Wi-Fi CERTIFIED 7™

A-MPDU with A-MSDU

BSRP Trigger frame

BSS critical update

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL OFDMA

Dynamic MU SMPS

EMLSR (Enhanced Multilink Single-Radio)

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MCS 12-13 Rx

MCS 12-13 Tx

Multi-RU

MU-RTS Trigger frame

Operating mode indication

Static puncturing

STR (Simultaneous Transmit and Receive)

SU-MIMO

Triggered uplink access optimization

**UL OFDMA** 



Wi-Fi Enhanced Open™ 2023-12

## **Wi-Fi CERTIFIED™ Certificate**



**Certification ID: WFA131171** 

## **Role: Access Point** Page 5 of 5 Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac A-MPDU with A-MSDU LDPC Rx LDPC Tx MCS 8-9 Rx Short Guard Interval STBC SU beamformer Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n A-MPDU Tx **OBSS** on Extension Channel Short Guard Interval STBC