



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA135305

Product Info

Date of Certification March 4, 2025

Company Huawei Technologies Co., Ltd.

Product Name Wireless LAN Access Point

Product Model Variant AirEngine6776-58TI-K

Model Number AirEngine6776-58TI-K

Category Routers

Sub-category Enterprise/Service Provider Access Point, Switch/Controller or Router

Summary of Certifications

CLASSIFICATION CERTIFICATION

Network management WMM®

Wi-Fi Agile Multiband™

Security Protected Management Frames

WPA2[™]-Enterprise 2018-04 WPA2[™]-Personal 2021-01 WPA3[™]-Enterprise 2022-12 WPA3[™]-Personal 2023-12

Wi-Fi (MAC/PHY) 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities6 GHz Spectrum Capabilities

Wi-Fi CERTIFIED 6®
Wi-Fi CERTIFIED 7™
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n



Certification ID: WFA135305



Role: Access Point	Page 2 of 4
Wi-Fi Components	
Wi-Fi Component Operating System	RF Architecture
HongMeng	Bands Supported Transmit (Tx) Receive (R:
Wi-Fi Component Firmware Ver.A	2.4 GHz 2 2
	5 GHz 4 4
	6 GHz 2 2
Certifications	
2.4 GHz Spectrum Capabilities	WPA2™-Enterprise 2018-04 (continued)
20 MHz Channel Width in 2.4 GHz	EAP methods
40 MHz Channel Width in 2.4 GHz	
5 GHz Spectrum Capabilities	WPA2™-Personal 2021-01
20 MHz Channel Width in 5 GHz	WPA3™-Enterprise 2022-12
40 MHz Channel Width in 5 GHz	EAP methods
80 MHz Channel Width in 5 GHz 160 MHz Channel Width in 5 GHz	192-bit security
	WPA3™-Personal 2023-12
6 GHz Spectrum Capabilities	AKM 24
20 MHz Channel Width in 6 GHz	Beacon Protection
40 MHz Channel Width in 6 GHz 80 MHz Channel Width in 6 GHz	
	Wi-Fi Agile Multiband™
Protected Management Frames	Wi-Fi CERTIFIED 6®
WMM®	4 antenna support
WPA2™-Enterprise 2018-04	A-MPDU with A-MSDU Basic Trigger frame in HE MU PPDU



Certification ID: WFA135305



Role: Access Point Page 3 of 4

Wi-Fi CERTIFIED 6® (continued)

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

DL OFDMA

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

Operating mode subfield in A-Control field

Operating mode indication

Operating mode UL MU Rx

SU-MIMO

UL OFDMA

Wi-Fi 6E

Co-located BSS

Wi-Fi CERTIFIED 7™

A-MPDU with A-MSDU

BSRP Trigger frame

BSS critical update

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

Compressed Block Ack Rx (buffer size 512)

Compressed Block Ack Tx (buffer size 512)

DL MU-MIMO

DL OFDMA

Dynamic MU SMPS

EMLSR (Enhanced Multilink Single-Radio)

LDPC Rx

Wi-Fi CERTIFIED 7™ (continued)

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

Multi-RU

Operating mode indication

Static puncturing

STR (Simultaneous Transmit and Receive)

SU-MIMO

Triggered uplink access optimization

UL MU-MIMO

UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

LDPC Tx

MCS 8-9 Rx

RTS with BW Signaling

Short Guard Interval

STBC

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx



Certification ID: WFA135305



Role: Access Point Page 4 of 4

Wi-Fi CERTIFIED™ n (continued)

HT Duplicate Mode
OBSS on Extension Channel
Short Guard Interval
STBC