



Wi-Fi CERTIFIED™ Certificate



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA135468

Product Info

Date of Certification	March 10, 2025
Company	Cisco Systems
Product Name	Cisco Catalyst 9800-40 Wireless Controller and Cisco CW9172H AP
Product Model Variant	Cisco IOS XE: 17.17
Model Number	C9800-40 and CW9172H
Category	Routers
Sub-category	Enterprise/Service Provider Access Point, Switch/Controller or Router

Summary of Certifications

CLASSIFICATION	CERTIFICATION
Connectivity	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities 6 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Release 2 Wi-Fi CERTIFIED 7™ Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n Wi-Fi Enhanced Open™ 2023-12
Optimization	WMM® WMM®-Power Save Wi-Fi Agile Multiband™
Security	Protected Management Frames WPA2™-Enterprise 2018-04 WPA2™-Personal 2021-01 WPA3™-Enterprise 2022-12 WPA3™-Personal 2024-10



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA135468



Summary of Certifications (continued)

Page 2 of 5

CLASSIFICATION

CERTIFICATION

Spectrum & Regulatory
Features

Spectrum & Regulatory



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA135468



Role: Access Point

Page 3 of 5

Wi-Fi Components

Wi-Fi Component Operating System

Linux, Version: 17.17

Wi-Fi Component Firmware

17.17

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2
6 GHz	2	2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz

40 MHz Channel Width in 5 GHz

80 MHz Channel Width in 5 GHz

160 MHz Channel Width in 5 GHz

6 GHz Spectrum Capabilities

Standard power operation

20 MHz Channel Width in 6 GHz

40 MHz Channel Width in 6 GHz

80 MHz Channel Width in 6 GHz

160 MHz Channel Width in 6 GHz

320 MHz channel width in 6 GHz

Protected Management Frames

Spectrum & Regulatory

Spectrum & Regulatory (continued)

802.11d

802.11h

WMM®

WMM®-Power Save

Legacy Power Save

Unschedule auto PS

WPA2™-Enterprise 2018-04

EAP methods

WPA2™-Personal 2021-01

WPA3™-Enterprise 2022-12

EAP methods

192-bit security

Fast Transition OTA on WPA3-Enterprise



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA135468



Role: Access Point

Page 4 of 5

WPA3™-Enterprise 2022-12 (continued)

Fast Transition OTA on WPA3-Enterprise transition mode
Fast Transition OTDS on WPA3-Enterprise

WPA3™-Personal 2024-10

AKM 24
AKM 25
Fast Transition OTA on WPA3-Personal
Fast Transition OTA on WPA3-Personal transition mode
Fast Transition OTDS on WPA3-Personal
Beacon Protection

Wi-Fi Agile Multiband™

Automatically populate BSS Transition candidate list
Fast Transition OTA on WPA2-Enterprise
Fast Transition OTA on WPA2-Personal

Wi-Fi CERTIFIED 6® Release 2

A-MPDU with A-MSDU
Beamforming sounding
BSRP Trigger frame
Compressed Block Ack Rx (buffer size 256)
Compressed Block Ack Tx (buffer size 256)
DL OFDMA
Individual Target Wake Time
LDPC Rx
LDPC Tx
MCS 8-9 Rx
MCS 8-9 Tx
MCS 10-11 Rx
MCS 10-11 Tx
MU EDCA Parameter Set element

Wi-Fi CERTIFIED 6® Release 2 (continued)

MU-BAR Trigger frame
MU-RTS Trigger frame
Operating mode subfield in A-Control field
Operating mode indication
Operating mode UL MU Rx
SU beamformer
SU-MIMO
UL OFDMA
Wi-Fi 6E
 Co-located BSS
 Multiple M-BSSID
Wi-Fi 6 Release 2 features
 UL MU Control
 UL Extended Range
 Target Wake Time information frames
 Extended sleep
 Dynamic MU SMPS

Wi-Fi CERTIFIED 7™

A-MPDU with A-MSDU
Beamforming sounding
BSRP Trigger frame
BSS critical update
Compressed Block Ack Rx (buffer size 256)
Compressed Block Ack Tx (buffer size 256)
Compressed Block Ack Rx (buffer size 512)
Compressed Block Ack Tx (buffer size 512)
DL OFDMA
Dynamic MU SMPS
EMLSR (Enhanced Multilink Single-Radio)
LDPC Rx
LDPC Tx
MCS 8-9 Rx
MCS 8-9 Tx



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA135468



Role: Access Point

Page 5 of 5

Wi-Fi CERTIFIED 7™ (continued)

MCS 10-11 Rx
MCS 10-11 Tx
MCS 12-13 Tx
Multi-RU
MU-RTS Trigger frame
Operating mode indication
 Operating mode indication for 320 MHz
Static puncturing
STR (Simultaneous Transmit and Receive)
SU-MIMO
Triggered uplink access optimization
UL OFDMA

Wi-Fi CERTIFIED™ n (continued)

OBSS on Extension Channel
Short Guard Interval
STBC

Wi-Fi Enhanced Open™ 2023-12

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU
Extended 5 GHz Channel Support
LDPC Rx
LDPC Tx
MCS 8-9 Rx
RTS with BW Signaling
Short Guard Interval
STBC
SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx