



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

# **Certification ID: WFA135470**

# **Product Info**

**Date of Certification** March 10, 2025

Company Cisco Systems

Product Name Cisco Catalyst 9800 Cloud Wireless Controller and Cisco CW9172H AP

Product Model Variant Cisco IOS XE: 17.17

Model Number C9800-CL and CW9172H

**Category** Routers

**Sub-category** Enterprise/Service Provider Access Point, Switch/Controller or Router

# **Summary of Certifications**

CLASSIFICATION CERTIFICATION

**Connectivity** 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities6 GHz Spectrum CapabilitiesWi-Fi CERTIFIED 6® Release 2

Wi-Fi CERTIFIED 7™
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n

Wi-Fi Enhanced Open™ 2023-12

**Optimization** WMM®

WMM®-Power Save Wi-Fi Agile Multiband™

**Security** Protected Management Frames

WPA2<sup>™</sup>-Enterprise 2018-04 WPA2<sup>™</sup>-Personal 2021-01 WPA3<sup>™</sup>-Enterprise 2022-12 WPA3<sup>™</sup>-Personal 2024-10



**Certification ID: WFA135470** 



# **Summary of Certifications (continued)**

Page 2 of 5

**CLASSIFICATION** 

**CERTIFICATION** 

**Spectrum & Regulatory** 

Spectrum & Regulatory

**Features** 



**Certification ID: WFA135470** 



Role: Access Point	Page 3 of 5
Wi-Fi Components	
Wi-Fi Component Operating System Linux, Version: 17.17	RF Architecture
Wi-Fi Component Firmware	Bands Supported Transmit (Tx) Receive (Rx)
17.17	2.4 GHz 2 2
	5 GHz 2 2
	6 GHz 2 2
Certifications	<u> </u>
2.4 GHz Spectrum Capabilities	Spectrum & Regulatory (continued)
20 MHz Channel Width in 2.4 GHz	802.11d 802.11h
5 GHz Spectrum Capabilities	
20 MHz Channel Width in 5 GHz	WMM®
40 MHz Channel Width in 5 GHz	WMM®-Power Save
80 MHz Channel Width in 5 GHz 160 MHz Channel Width in 5 GHz	Legacy Power Save Unschedule auto PS
6 GHz Spectrum Capabilities	

## 6 GHz Spectrum Capabilities

Standard power operation
20 MHz Channel Width in 6 GHz
40 MHz Channel Width in 6 GHz
80 MHz Channel Width in 6 GHz
160 MHz Channel Width in 6 GHz
320 MHz channel width in 6 GHz

## **Protected Management Frames**

**Spectrum & Regulatory** 

# WPA2™-Enterprise 2018-04

EAP methods

## WPA2™-Personal 2021-01

## WPA3™-Enterprise 2022-12

EAP methods 192-bit security

Fast Transition OTA on WPA3-Enterprise



Certification ID: WFA135470



Role: Access Point Page 4 of 5

## WPA3™-Enterprise 2022-12 (continued)

Fast Transition OTA on WPA3-Enterprise transition mode Fast Transition OTDS on WPA3-Enterprise

#### WPA3™-Personal 2024-10

AKM 24

AKM 25

Fast Transition OTA on WPA3-Personal

Fast Transition OTA on WPA3-Personal transition mode

Fast Transition OTDS on WPA3-Personal

Beacon Protection

#### Wi-Fi Agile Multiband™

Automatically populate BSS Transition candidate list

Fast Transition OTA on WPA2-Enterprise

Fast Transition OTA on WPA2-Personal

#### Wi-Fi CERTIFIED 6® Release 2

A-MPDU with A-MSDU

Beamforming sounding

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL OFDMA

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

#### Wi-Fi CERTIFIED 6® Release 2 (continued)

MU-BAR Trigger frame

MU-RTS Trigger frame

Operating mode subfield in A-Control field

Operating mode indication

Operating mode UL MU Rx

SU beamformer

SU-MIMO

**UL OFDMA** 

Wi-Fi 6E

Co-located BSS

Multiple M-BSSID

Wi-Fi 6 Release 2 features

**UL MU Control** 

**UL Extended Range** 

Target Wake Time information frames

Extended sleep

Dynamic MU SMPS

## Wi-Fi CERTIFIED 7™

A-MPDU with A-MSDU

Beamforming sounding

**BSRP** Trigger frame

BSS critical update

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

Compressed Block Ack Rx (buffer size 512)

Compressed Block Ack Tx (buffer size 512)

DL OFDMA

Dynamic MU SMPS

EMLSR (Enhanced Multilink Single-Radio)

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx



**Certification ID: WFA135470** 



Role: Access Point Page 5 of 5

## Wi-Fi CERTIFIED 7™ (continued)

MCS 10-11 Rx

MCS 10-11 Tx

MCS 12-13 Tx

Multi-RU

MU-RTS Trigger frame

Operating mode indication

Operating mode indication for 320 MHz

Static puncturing

STR (Simultaneous Transmit and Receive)

SU-MIMC

Triggered uplink access optimization

**UL OFDMA** 

## Wi-Fi CERTIFIED™ a

#### Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU

Extended 5 GHz Channel Support

LDPC Rx

LDPC Tx

MCS 8-9 Rx

RTS with BW Signaling

Short Guard Interval

STBC

SU beamformer

#### Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx

# Wi-Fi CERTIFIED™ n (continued)

OBSS on Extension Channel

Short Guard Interval

**STBC** 

# Wi-Fi Enhanced Open™ 2023-12