Wi-Fi CERTIFIED™ Certificate

This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA135680

Product Info

Date of Certification	April 22, 2025
Company	TCL Communication Ltd.
Product Name	HH516V
Product Model Variant	HH516V
Model Number	HH516V
Category	Routers
Sub-category	Access Point for Home or Small Office (Wireless Router)

Summary of Certifications

CLASSIFICATION	CERTIFICATION
Connectivity	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Release 2 Wi-Fi CERTIFIED 7™ Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n
Optimization	WMM® Wi-Fi Agile Multiband™
Security	Protected Management Frames WPA2™-Personal 2021-01 WPA3™-Personal 2024-10
Spectrum & Regulatory Features	Spectrum & Regulatory

Wi-Fi Components

Wi-Fi Component Operating System

Linux 5.15 (OpenWrt 23.05)

Wi-Fi Component Firmware

FW ver: 0x0

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	4	4
5 GHz	4	4

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz
40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz
160 MHz Channel Width in 5 GHz

Protected Management Frames

Spectrum & Regulatory

802.11d
802.11h

WMM®

WPA2™-Personal 2021-01

WPA3™-Personal 2024-10

WPA3™-Personal 2024-10 (continued)

AKM 24
Beacon Protection

Wi-Fi Agile Multiband™

Automatically populate BSS Transition candidate list

Wi-Fi CERTIFIED 6® Release 2

4 antenna support
A-MPDU with A-MSDU
Basic Trigger frame in HE MU PPDU
BSRP Trigger frame
Compressed Block Ack Rx (buffer size 256)
Compressed Block Ack Tx (buffer size 256)
DL MU-MIMO
DL OFDMA
Individual Target Wake Time
LDPC Rx
LDPC Tx
MCS 8-9 Rx
MCS 8-9 Tx
MCS 10-11 Rx

Wi-Fi CERTIFIED 6® Release 2 (continued)

MCS 10-11 Tx

MU EDCA Parameter Set element

MU-RTS Trigger frame

M-BSSID

Operating mode subfield in A-Control field

Operating mode indication

Operating mode UL MU Rx

SU beamformer

SU-MIMO

TXOP RTS Threshold

UL OFDMA

Wi-Fi 6 Release 2 features

- UL MU-MIMO
- Target Wake Time information frames
- Dynamic MU SMPS

Wi-Fi CERTIFIED 7™

Advertised TID-to-link mapping

A-MPDU with A-MSDU

BSRP Trigger frame

BSS critical update

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

Compressed Block Ack Rx (buffer size 512)

Compressed Block Ack Tx (buffer size 512)

DL MU-MIMO

DL OFDMA

Dynamic MU SMPS

EMLSR (Enhanced Multilink Single-Radio)

EPCS (Emergency Preparedness Communications Services) priority access

LDPC Rx

LDPC Tx

Load Balancing in MLO

Wi-Fi CERTIFIED 7™ (continued)

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MCS 12-13 Rx

MCS 12-13 Tx

Multi-link reconfiguration – AP removal

Multi-link reconfiguration – AP restart

Multi-RU

MU-RTS Trigger frame

Operating mode indication

Static puncturing

STR (Simultaneous Transmit and Receive)

SU-MIMO

Triggered uplink access optimization

UL MU-MIMO

UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU

DL MU-MIMO

Extended 5 GHz Channel Support

LDPC Rx

LDPC Tx

MCS 8-9 Rx

RTS with BW Signaling

Short Guard Interval

STBC

SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx

OBSS on Extension Channel

Short Guard Interval

STBC