



Wi-Fi CERTIFIED™ Certificate

This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs



Certification ID: WFA93397

Product Info

Date of Certification	January 20, 2020
Company	Oppo
Product Name	Mobile Phone
Product Model Variant	2020-01-20 (WFA93397 - 10168034)
Model Number	CPH2025
Category	Phones
Sub-category	Smartphone

Summary of Certifications

CLASSIFICATION	CERTIFICATION
Connectivity	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n
Optimization	WMM® Wi-Fi Agile Multiband™
Security	Protected Management Frames WPA2™-Enterprise 2018-04 WPA2™-Personal 2018-04 WPA3™-Enterprise 2018-04 WPA3™-Personal 2019-08 WPA™-Enterprise WPA™-Personal



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA93397



Role: Station

Page 2 of 3

Wi-Fi Components

Wi-Fi Component Operating System

Android, version:Android 10

Wi-Fi Component Firmware

1.0.1.0.247.0

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz
40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz

Protected Management Frames

WMM®

WPA2™-Enterprise 2018-04

EAP methods
EAP AKA
EAP AKA Prime
EAP SIM
EAP TLS
EAP TTLS
PEAPv0
PEAPv1

WPA2™-Personal 2018-04

WPA3™-Enterprise 2018-04

EAP methods
EAP AKA
EAP AKA Prime
EAP SIM
EAP TLS
EAP TTLS
PEAPv0
PEAPv1

WPA3™-Personal 2019-08

WPA™-Enterprise

WPA™-Personal

Wi-Fi Agile Multiband™

ANQP
Beacon Report Measurement Active Mode
Beacon Report Measurement Passive Mode
BTM Query
Cellular Data capable



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA93397



Role: Station

Page 3 of 3

Wi-Fi Agile Multiband™ (continued)

Fast Transition OTA on WPA2-Personal

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU
BSRP Trigger frame
Compressed Block Ack Rx (buffer size 256)
Compressed Block Ack Tx (buffer size 256)
DL Mu PPDU multi-tone
DL MU-MIMO
HE NDP
Individual Target Wake Time
LDPC Rx
LDPC Tx
MCS 8-9 Rx
MCS 8-9 Tx
MCS 10-11 Rx
MCS 10-11 Tx
MU EDCA Parameter Set element
MU-BAR Trigger frame
MU-RTS Trigger frame
OM Control field Tx
OM subfield in A-Control field
Operating Mode indication
SU beamformee
UL OFDMA
UL TB PPDU multi-tone

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

Extended 5 GHz Channel Support
A-MPDU with A-MSDU
DL MU-MIMO

Wi-Fi CERTIFIED™ ac (continued)

LDPC Rx
MCS 8-9 Rx
Short Guard Interval
STBC
LDPC Tx
SU beamformee

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

STBC
A-MPDU Tx
OBSS on Extension Channel
Short Guard Interval