Wi-Fi CERTIFIED® Certificate

This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org

Certification ID: WFA100148

Product Info

Date of Certification	November 5, 2020
Company	MediaTek Inc.
Product Name	MT7921
Product Model Variant	2020-11-05 (WFA100148 - 11214038)
Model Number	MT7921
Category	Other
Sub-category	Reference Design

Summary of Certifications

CLASSIFICATION	CERTIFICATION
Access	Wi-Fi Protected Setup™
Alternative topologies	Wi-Fi Direct®
Network management	WMM® Wi-Fi Agile Multiband™
Security	Protected Management Frames WPA2™-Enterprise 2018-04 WPA2™-Personal 2018-04 WPA3™-Enterprise 2018-04 WPA3™-Personal 2019-08
Wi-Fi (MAC/PHY)	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Spectrum & Regulatory Wi-Fi CERTIFIED 6® Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n

Wi-Fi CERTIFIED® Certificate

Certification ID: WFA100148

Wi-Fi Components

Wi-Fi Component Operating System
Windows 10

Wi-Fi Component Firmware
Windows 10

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz
40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz

Protected Management Frames

Spectrum & Regulatory

802.11h

WMM®

WPA2™-Enterprise 2018-04

EAP methods
    EAP TLS
    PEAPv0

WPA2™-Personal 2018-04

WPA3™-Enterprise 2018-04

EAP methods
    EAP TLS
    PEAPv0

WPA3™-Personal 2019-08

Wi-Fi Agile Multiband™

Beacon Report Measurement Passive Mode

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU
BSRP Trigger frame
Compressed Block Ack Rx (buffer size 256)
Compressed Block Ack Tx (buffer size 256)
DL MU-MIMO
Individual Target Wake Time
LDPC Rx
LDPC Tx
MCS 8-9 Rx

Wi-Fi CERTIFIED 6® (continued)

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

MU-RTS Trigger frame

M-BSSID

Operating mode control field

Operating mode subfield in A-Control field

SU beamformee

UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

Extended 5 GHz Channel Support

RTS with BW Signaling

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

MCS 8-9 Rx

Short Guard Interval

LDPC Tx

SU beamformee

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx

HT Duplicate Mode

Wi-Fi CERTIFIED™ n (continued)

OBSS on Extension Channel

Power Management

Short Guard Interval

Wi-Fi Direct®

Wi-Fi Protected Setup™

PIN