



Wi-Fi CERTIFIED™ Certificate

This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs



Certification ID: WFA101124

Product Info

Date of Certification	January 7, 2021
Company	MediaTek Inc.
Product Name	MT7915STA
Product Model Variant	2020-07-17 (WFA101124 - 11391079)
Model Number	MT7915
Category	Other
Sub-category	Reference Design

Summary of Certifications

CLASSIFICATION	CERTIFICATION
Connectivity	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n Wi-Fi Enhanced Open™ 2020-02
Optimization	WMM® Wi-Fi Agile Multiband™
Security	Protected Management Frames WPA2™-Enterprise 2018-04 WPA2™-Personal 2020-02 WPA3™-Enterprise 2020-02 WPA3™-Personal 2020-02 WPA™-Enterprise WPA™-Personal



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA101124



Role: Station

Page 2 of 3

Wi-Fi Components

Wi-Fi Component Operating System

Linux

Wi-Fi Component Firmware

8a01

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz

40 MHz Channel Width in 5 GHz

80 MHz Channel Width in 5 GHz

Protected Management Frames

WMM®

WPA2™-Enterprise 2018-04

EAP methods

EAP TLS

WPA2™-Personal 2020-02

WPA3™-Enterprise 2020-02

EAP methods

WPA3™-Enterprise 2020-02 (continued)

EAP TLS

Server Certificate Validation

WPA3™-Personal 2020-02

WPA™-Enterprise

WPA™-Personal

Wi-Fi Agile Multiband™

Beacon Report Measurement Active Mode

Beacon Report Measurement Passive Mode

BTM Query

Cellular Data capable

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL Mu PPDU multi-tone



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA101124



Role: Station

Page 3 of 3

Wi-Fi CERTIFIED 6® (continued)

DL MU-MIMO
Individual Target Wake Time
LDPC Rx
LDPC Tx
MCS 8-9 Rx
MCS 8-9 Tx
MCS 10-11 Rx
MCS 10-11 Tx
MU EDCA Parameter Set element
MU-BAR Trigger frame
MU-RTS Trigger frame
OM Control field Tx
OM subfield in A-Control field
Operating Mode indication
SU beamformee
UL OFDMA
UL TB PPDU multi-tone

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

Extended 5 GHz Channel Support
RTS with BW Signaling
A-MPDU with A-MSDU
DL MU-MIMO
LDPC Rx
MCS 8-9 Rx
Short Guard Interval
STBC
LDPC Tx
SU beamformee

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

STBC
A-MPDU Tx
OBSS on Extension Channel
Short Guard Interval

Wi-Fi Enhanced Open™ 2020-02