



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org

Certification ID: WFA103759

Product Info

Date of Certification January 8, 2021

Company MediaTek Inc.

Product Name MT7921K

Product Model Variant Wi-Fi 6E

Model Number MT7921K, RZ608

Category Other

Sub-category Reference Design

Summary of Certifications

CLASSIFICATION CERTIFICATION

Access Wi-Fi Protected Setup™

Alternative topologies Wi-Fi Direct®

Network management WMM®

WMM®-Power Save Wi-Fi Agile Multiband™

Security Protected Management Frames

WPA2[™]-Enterprise 2018-04 WPA2[™]-Personal 2020-02 WPA3[™]-Enterprise 2020-02 WPA3[™]-Personal 2020-02

Wi-Fi Enhanced Open™ 2020-02

Wi-Fi (MAC/PHY) 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities6 GHz Spectrum Capabilities

Spectrum & Regulatory Wi-Fi CERTIFIED 6® Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b



Certification ID: WFA103759



Summary of Certifications (continued)		Page 2 of 4
CLASSIFICATION	CERTIFICATION	
Wi-Fi (MAC/PHY)	Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n	



Certification ID: WFA103759



Role: Station		Pa	age 3 of 4
Wi-Fi Components			
Wi-Fi Component Operating System	RF Architecture		
Windows 10	Bands Supported	Transmit (Tx)	Receive (Rx)
Wi-Fi Component Firmware	2.4 GHz	2	2
Windows	5 GHz	2	2
	6 GHz	2	2
Certifications			
2.4 GHz Spectrum Capabilities	WMM®		
20 MHz Channel Width in 2.4 GHz 40 MHz Channel Width in 2.4 GHz	WMM®-Power Save		
	WPA2™-Enterpris	se 2018-04	
5 GHz Spectrum Capabilities	EAP methods		
20 MHz Channel Width in 5 GHz	EAP TLS PEAPv0		
40 MHz Channel Width in 5 GHz 80 MHz Channel Width in 5 GHz	T LAI VO		
SO III IZ SIIGIIII O VIIGII II O SIIZ	WPA2™-Persona	l 2020-02	
6 GHz Spectrum Capabilities	WPA3™-Enterpris	se 2020-02	
20 MHz Channel Width in 6 GHz	EAP methods		
40 MHz Channel Width in 6 GHz 80 MHz Channel Width in 6 GHz	EAP TLS		
	PEAPv0 Server Certificate Validation		
Protected Management Frames			
Spectrum & Regulatory	WPA3™-Persona	2020-02	
802.11h	Wi-Fi Agile Multib	and™	
	Beacon Report Measurement Passive Mode		



Certification ID: WFA103759



Role: Station Page 4 of 4

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

MU-RTS Trigger frame

M-BSSID

Operating mode subfield in A-Control field

SU beamformee

UL OFDMA

Wi-Fi 6E

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

Extended 5 GHz Channel Support

RTS with BW Signaling

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

MCS 8-9 Rx

Short Guard Interval

LDPC Tx

SU beamformee

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

A-MPDU Tx

HT Duplicate Mode

OBSS on Extension Channel

Short Guard Interval

Wi-Fi Direct®

Wi-Fi Enhanced Open™ 2020-02

Wi-Fi Protected Setup™

PIN

Pushbutton