

# Wi-Fi CERTIFIED® Certificate



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org

## **Certification ID: WFA91193**

### **Product Info**

**Date of Certification** March 3, 2020

**Company** EnGenius Technologies, Inc.

Product Name AX1800 Ceiling Mount Managed Access Point

**Product Model Variant** 2020-03-03 (WFA91193 - 10679919)

Model Number EWS357AP

**Category** Routers

Sub-category Enterprise/Service Provider Access Point, Switch/Controller or Router

## **Summary of Certifications**

CLASSIFICATION CERTIFICATION

Access Passpoint® Release 2

Network management WMM®

Wi-Fi Agile Multiband™

Security Protected Management Frames

WPA2<sup>™</sup>-Enterprise 2018-04 WPA2<sup>™</sup>-Personal 2018-04 WPA3<sup>™</sup>-Enterprise 2018-04 WPA3<sup>™</sup>-Personal 2019-08 Wi-Fi Enhanced Open<sup>™</sup> 2018-04

'

Wi-Fi (MAC/PHY) 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities

Wi-Fi CERTIFIED 6®
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n



# Wi-Fi CERTIFIED® Certificate

**Certification ID: WFA91193** 



Role: Access Point	Page 2 of 3
--------------------	-------------

W	i-F	i C	om	por	nents
---	-----	-----	----	-----	-------

Wi-Fi Component Operating System

Linux

Wi-Fi Component Firmware

V.3

#### **RF Architecture**

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2

#### Certifications

## 2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz 40 MHz Channel Width in 2.4 GHz

#### WPA3™-Enterprise 2018-04

EAP methods 192-bit security

#### **5 GHz Spectrum Capabilities**

20 MHz Channel Width in 5 GHz 40 MHz Channel Width in 5 GHz 80 MHz Channel Width in 5 GHz

## WPA3™-Personal 2019-08

Wi-Fi Agile Multiband™

# Automatically populate BSS Transition candidate list

#### Passpoint® Release 2

Online Sign Up and Policy provisioning

#### Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU

Cellular Data aware

Basic Trigger frame in HE MU PPDU

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

DL OFDMA

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

#### **Protected Management Frames**

**WMM®** 

#### WPA2™-Enterprise 2018-04

EAP methods

WPA2™-Personal 2018-04



# Wi-Fi CERTIFIED® Certificate

**Certification ID: WFA91193** 



Role: Access Point Page 3 of 3

## Wi-Fi CERTIFIED 6® (continued)

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

Operating mode subfield in A-Control field

Operating mode indication

Operating mode UL MU Rx

SU beamformer

SU-MIMO

TXOP RTS Threshold

**UL OFDMA** 

#### Wi-Fi CERTIFIED™ a

#### Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

LDPC Tx

MCS 8-9 Rx

Short Guard Interval

STBC

SU beamformer

#### Wi-Fi CERTIFIED™ b

#### Wi-Fi CERTIFIED™ g

## Wi-Fi CERTIFIED™ n

**OBSS** on Extension Channel

**Short Guard Interval** 

## Wi-Fi CERTIFIED™ n (continued)

STBC

A-MPDU Tx

Wi-Fi Enhanced Open™ 2018-04