Wi-Fi CERTIFIED™ Certificate

This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA97555

Product Info

Date of Certification	July 13, 2020
Company	Huawei Technologies Co., Ltd.
Product Name	Huawei AirEngine6760R-51E with Huawei Access Controller
Product Model Variant	2020-07-13 (WFA97555 - 11369842)
Model Number	AirEngine6760R-51E
Category	Routers
Sub-category	Enterprise/Service Provider Access Point, Switch/Controller or Router

Summary of Certifications

CLASSIFICATION	CERTIFICATION
Network management	WMM® WMM®-Power Save Wi-Fi Agile Multiband™
Security	Protected Management Frames WPA2™-Enterprise 2018-04 WPA2™-Personal 2018-04 WPA3™-Enterprise 2018-04 WPA3™-Personal 2019-08
Wi-Fi (MAC/PHY)	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Spectrum & Regulatory Wi-Fi CERTIFIED 6® Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n

Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA97555

Wi-Fi Components

Wi-Fi Component Operating System

Linux

Wi-Fi Component Firmware

Ver.A

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	4	4
5 GHz	4	4

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz
40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz
160 MHz Channel Width in 5 GHz

Protected Management Frames

Spectrum & Regulatory

802.11d

WMM®

WMM®-Power Save

Legacy Power Save
Unschedule auto PS

WPA2™-Enterprise 2018-04

EAP methods

WPA2™-Personal 2018-04

WPA3™-Enterprise 2018-04

EAP methods
192-bit security

WPA3™-Personal 2019-08

Wi-Fi Agile Multiband™

Wi-Fi CERTIFIED 6®

4 antenna support
A-MPDU with A-MSDU
Compressed Block Ack Rx (buffer size 256)
Compressed Block Ack Tx (buffer size 256)
DL MU-MIMO
DL OFDMA
Individual Target Wake Time
LDPC Rx

Wi-Fi CERTIFIED 6® (continued)

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MU EDCA Parameter Set element

MU-BAR Trigger frame

Operating mode subfield in A-Control field

Operating mode indication

Operating mode UL MU Rx

SU beamformer

SU-MIMO

TXOP RTS Threshold

UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

Extended 5 GHz Channel Support

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

LDPC Tx

MCS 8-9 Rx

Short Guard Interval

STBC

SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

Wi-Fi CERTIFIED™ n (continued)

OBSS on Extension Channel

Short Guard Interval

STBC

A-MPDU Tx