



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

## **Certification ID: WFA94617**

#### **Product Info**

**Date of Certification** March 24, 2021

Company Extreme Networks

Product Name AP410C

**Product Model Variant** 2020-10-06 (WFA94617 - 11686935)

Model Number AP410C

**Category** Routers

**Sub-category** Enterprise/Service Provider Access Point, Switch/Controller or Router

## **Summary of Certifications**

CLASSIFICATION CERTIFICATION

Access Passpoint® Release 2

**Connectivity** 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities

Wi-Fi CERTIFIED 6®
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ ac
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n

Optimization WMM®

WMM®-Power Save Wi-Fi Agile Multiband™

**Security** Protected Management Frames

WPA2<sup>™</sup>-Enterprise 2018-04 WPA2<sup>™</sup>-Personal 2021-01 WPA3<sup>™</sup>-Enterprise 2018-04 WPA3<sup>™</sup>-Personal 2019-08

WPA™-Enterprise WPA™-Personal





**Certification ID: WFA94617** 

Summary	of	<b>Certifications</b>	(continued)
Sullilliai y	U	oei iiiicalioiis	(COIILIIIUEU)

Page 2 of 4

CLASSIFICATION

**CERTIFICATION** 

Spectrum & Regulatory

Spectrum & Regulatory

**Features** 





**Certification ID: WFA94617** 

Role: Access Point		Pa	age 3 of 4	
Vi-Fi Components				
Wi-Fi Component Operating System	RF Architecture			
Proprietary / Other, version:10.3r2, description:HiveOS	Bands Supported	Transmit (Tx)	Receive (Rx)	
Wi-Fi Component Firmware	2.4 GHz	2	2	
HiveOS 10.3r2	5 GHz	4	4	
Certifications				
2.4 GHz Spectrum Capabilities	WMM®-Power Save			
20 MHz Channel Width in 2.4 GHz	Legacy Power Save			
5 GHz Spectrum Capabilities	Unschedule auto PS			
	WPA2™-Enterprise	2018-04		
20 MHz Channel Width in 5 GHz 40 MHz Channel Width in 5 GHz	EAP methods			
80 MHz Channel Width in 5 GHz				
160 MHz Channel Width in 5 GHz	WPA2™-Personal 2	021-01		
Passpoint® Release 2	WPA3™-Enterprise	2018-04		
Online Sign Up and Policy provisioning	EAP methods			
Protected Management Frames	WPA3™-Personal 2	019-08		
Spectrum & Regulatory	WPA™-Enterprise			
802.11d 802.11h	WPA™-Personal			
002.1111	Wi-Fi Agile Multibar	nd™		
WMM®	Automotically paradets DO	Automatically populate BSS Transition candidate list		





### **Certification ID: WFA94617**

Role: Access Point Page 4 of 4

#### Wi-Fi Agile Multiband™ (continued)

Fast Transition OTA on WPA2-Enterprise Fast Transition OTA on WPA2-Personal

#### Wi-Fi CERTIFIED 6®

4 antenna support

A-MPDU with A-MSDU

Basic Trigger frame in HE MU PPDU

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

DL OFDMA

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

MU-RTS Trigger frame

Operating Mode indication

SU beamformer

TXOP RTS Threshold

**UL OFDMA** 

#### Wi-Fi CERTIFIED™ a

#### Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

#### Wi-Fi CERTIFIED™ ac (continued)

LDPC Tx

MCS 8-9 Rx

Short Guard Interval

STBC

SU beamformer

#### Wi-Fi CERTIFIED™ b

#### Wi-Fi CERTIFIED™ g

#### Wi-Fi CERTIFIED™ n

HT Duplicate Mode

**OBSS** on Extension Channel

Short Guard Interval

STBC

A-MPDU Tx