

Wi-Fi CERTIFIED™ Certificate



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA101804

Product Info

Date of Certification November 11, 2020

Company NEC Corporation

Product Name NEC QX-W1130

Product Model Variant 2020-11-11 (WFA101804 - 11940833)

Model Number NEC QX-W1130

Category Routers

Sub-category Enterprise/Service Provider Access Point, Switch/Controller or Router

Summary of Certifications

Connectivity 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities

Wi-Fi CERTIFIED 6®
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n

Optimization WMM®

WMM®-Power Save Wi-Fi Agile Multiband™

Security Protected Management Frames

WPA2[™]-Enterprise 2018-04 WPA2[™]-Personal 2018-04 WPA3[™]-Enterprise 2018-04 WPA3[™]-Personal 2019-08

WPA™-Enterprise WPA™-Personal

Spectrum & Regulatory

Features

Spectrum & Regulatory



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA101804



Role: Access Point Page 2 of 3

Wi-Fi Components

Wi-Fi Component Operating System

Proprietary / Other, description:Comware

Wi-Fi Component Firmware

V700R001

RF Architecture

Bands Supported Transmit (Tx) Receive (Rx)

2.4 GHz 2 2

5 GHz 4 4

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz 40 MHz Channel Width in 2.4 GHz WMM®-Power Save (continued)

Unschedule auto PS

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz

40 MHz Channel Width in 5 GHz

80 MHz Channel Width in 5 GHz 160 MHz Channel Width in 5 GHz WPA2™-Personal 2018-04

WPA3™-Enterprise 2018-04

WPA2™-Enterprise 2018-04

Protected Management Frames

EAP methods

EAP methods

Spectrum & Regulatory

802.11d

802.11h

WPA3™-Personal 2019-08

WPA™-Enterprise

WPA™-Personal

Wi-Fi Agile Multiband™

Wi-Fi CERTIFIED 6®

WMM®

WMM®-Power Save

Legacy Power Save



Wi-Fi CERTIFIED™ Certificate



Role: Access Point Page 3 of 3

Wi-Fi CERTIFIED 6® (continued)

4 antenna support

A-MPDU with A-MSDU

Basic Trigger frame in HE MU PPDU

BSRP Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

DL OFDMA

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

MU-RTS Trigger frame

M-BSSID

Operating Mode indication

SU beamformer

TXOP RTS Threshold

UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

LDPC Tx

MCS 8-9 Rx

Short Guard Interval

STBC

Wi-Fi CERTIFIED™ ac (continued)

SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

OBSS on Extension Channel

Short Guard Interval

STBC

A-MPDU Tx