

# Wi-Fi CERTIFIED™ Certificate



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

### **Certification ID: WFA50431**

#### **Product Info**

**Date of Certification** September 20, 2013

**Company** Dell Technologies

Product Name Dell PowerConnect W-6000 Controller/Dell PowerConnect W-AP224

**Access Point** 

**Product Model Variant** 2013-09-20 (WFA50431 - 1321317)

Model Number W-6000/W-AP224

**Category** Routers

**Sub-category** Enterprise/Service Provider Access Point, Switch/Controller or Router

## **Summary of Certifications**

CLASSIFICATION CERTIFICATION

**Connectivity** 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities

Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n

**Optimization** WMM®

WMM®-Power Save

Security WPA2™-Enterprise

WPA2™-Personal

**Spectrum & Regulatory** 

Spectrum & Regulatory

**Features** 



# **Wi-Fi CERTIFIED™ Certificate**





| Role: Access Point  | Page 2 of 2          |                |              |  |
|---|----------------------|----------------|--------------|--|
| Wi-Fi Components  |                      |                |              |  |
| Wi-Fi Component Operating System                                | RF Architecture      |                |              |  |
| Proprietary / Other, version:6.3.0.0, description:Aruba OS      | Bands Supported      | Transmit (Tx)  | Receive (Rx) |  |
| Wi-Fi Component Firmware  | 2.4 GHz              | 3              | 3            |  |
| (empty)   | 5 GHz                | 3              | 3            |  |
| Certifications  |                      |                |              |  |
| 2.4 GHz Spectrum Capabilities                                   | WPA2™-Personal       |                |              |  |
| 20 MHz Channel Width in 2.4 GHz 40 MHz Channel Width in 2.4 GHz | Wi-Fi CERTIFIED™ a   |                |              |  |
|   | Wi-Fi CERTIFIED™ ac  |                |              |  |
| 5 GHz Spectrum Capabilities                                     | A-MPDU with A-MSDU   |                |              |  |
| 20 MHz Channel Width in 5 GHz                                   | LDPC Rx<br>LDPC Tx   |                |              |  |
| 40 MHz Channel Width in 5 GHz                                   | MCS 8-9 Rx           |                |              |  |
| 80 MHz Channel Width in 5 GHz                                   | Short Guard Interval |                |              |  |
| Spectrum & Regulatory   | SU beamformer        |                |              |  |
| 802.11d   | Wi-Fi CERTIFIED™     | <sup>™</sup> b |              |  |
| 802.11h   |                      |                |              |  |
| WMM®  | Wi-Fi CERTIFIED™     | <sup>™</sup> g |              |  |
|   | Wi-Fi CERTIFIED™     | n n            |              |  |
| WMM®-Power Save   | Short Guard Interval |                |              |  |
| WPA2™-Enterprise  | STBC<br>A-MPDU Tx    |                |              |  |
| EAP methods   |                      |                |              |  |