Wi-Fi CERTIFIED® Certificate

This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org

Certification ID: WFA100116

Product Info

Date of Certification	June 8, 2020
Company	Huawei Technologies Co., Ltd.
Product Name	Optical Network Terminal
Product Model Variant	2020-06-08 (WFA100116 - 11205582)
Model Number	OptiXstar HG8245Y6-4N
Category	Routers
Sub-category	Cable, DSL or Other Broadband Gateway (Integrated Home Access Device)

Summary of Certifications

CLASSIFICATION	CERTIFICATION
Access	Wi-Fi Protected Setup™
Alternative topologies	Wi-Fi EasyMesh™
Network management	WMM® WMM®-Power Save Wi-Fi Agile Multiband™
Security	Protected Management Frames WPA2™-Enterprise 2018-04 WPA2™-Personal 2018-04 WPA3™-Enterprise 2018-04 WPA3™-Personal 2019-08
Wi-Fi (MAC/PHY)	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n

Wi-Fi CERTIFIED® Certificate

Certification ID: WFA100116

Wi-Fi Components

Wi-Fi Component Operating System
Linux

Wi-Fi Component Firmware
V5

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz
40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz
160 MHz Channel Width in 5 GHz

Protected Management Frames

WMM®

WMM®-Power Save

Legacy Power Save
Unschedule auto PS

WPA2™-Enterprise 2018-04

EAP methods

WPA2™-Personal 2018-04

WPA3™-Enterprise 2018-04

EAP methods

WPA3™-Personal 2019-08

Wi-Fi Agile Multiband™

Automatically populate BSS Transition candidate list

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU
Basic Trigger frame in HE MU PPDU
BSRP Trigger frame
DL MU-MIMO
DL OFDMA
Individual Target Wake Time
LDPC Rx
LDPC Tx
MCS 8-9 Rx
MCS 8-9 Tx
MCS 10-11 Rx

Wi-Fi CERTIFIED 6® (continued)

MCS 10-11 Tx
MU-BAR Trigger frame
MU-RTS Trigger frame
Operating mode subfield in A-Control field
Operating mode indication
Operating mode UL MU Rx
SU beamformer
SU-MIMO
UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

RTS with BW Signaling
Extended 5 GHz Channel Support
A-MPDU with A-MSDU
DL MU-MIMO
LDPC Rx
LDPC Tx
MCS 8-9 Rx
Short Guard Interval
STBC
SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

OBSS on Extension Channel
Short Guard Interval
STBC

Wi-Fi CERTIFIED™ n (continued)

A-MPDU Tx

Wi-Fi EasyMesh™

Backhaul Link
    Backhaul in 2.4 GHz
    Backhaul in 5 GHz low band
    Backhaul in 5 GHz high band
    Backhaul over Ethernet
Fronthaul Access Point
    Fronthaul in 2.4 GHz
    Fronthaul in 5 GHz low band
    Fronthaul in 5 GHz high band
Client Capability Query
Unassociated STA Link Metrics Reporting
Backhaul onboarding with Wi-Fi Protected Setup pushbutton

Wi-Fi Protected Setup™

PIN
Pushbutton

Wi-Fi CERTIFIED® Certificate

Certification ID: WFA100116

Wi-Fi Components

Wi-Fi Component Operating System

Linux

Certifications

Wi-Fi EasyMesh™