



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

### **Certification ID: WFA94244**

### **Product Info**

**Date of Certification** May 26, 2020

Company Xiaomi Communications

Product Name Mi 10

Product Model Variant 2020-05-26 (WFA94244 - merged)

Model Number M2001J2G

**Category** Phones

**Sub-category** Smartphone

### **Summary of Certifications**

CLASSIFICATION CERTIFICATION

Access Wi-Fi Protected Setup™

**Applications & Services** Miracast®

**Connectivity** 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities

Wi-Fi CERTIFIED 6®
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n

Wi-Fi Direct®

**Optimization** WMM®

WMM®-Power Save Wi-Fi Agile Multiband™

**Security** Protected Management Frames

WPA2<sup>™</sup>-Enterprise 2018-04 WPA2<sup>™</sup>-Personal 2018-04 WPA3<sup>™</sup>-Enterprise 2018-04 WPA3<sup>™</sup>-Personal 2019-08





**Certification ID: WFA94244** 

Summary of Certifications (continued)		Page 2 of 7
CLASSIFICATION	CERTIFICATION	
Security	WPA™-Enterprise WPA™-Personal	





**Certification ID: WFA94244** 

Role: Access Point	Page 3 of 7
	. ago o o .

### Wi-Fi Components

**Wi-Fi Component Operating System** 

Android

Wi-Fi Component Firmware

1.0.1.0.247.0+

### **RF Architecture**

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2

### Certifications

### 2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz 40 MHz Channel Width in 2.4 GHz

### **5 GHz Spectrum Capabilities**

20 MHz Channel Width in 5 GHz 40 MHz Channel Width in 5 GHz 80 MHz Channel Width in 5 GHz

### **Protected Management Frames**

**WMM®** 

WPA2™-Personal 2018-04

WPA3™-Personal 2019-08

#### Wi-Fi CERTIFIED 6®

Compressed Block Ack Rx (buffer size 256)

LDPC Rx

LDPC Tx

MCS 8-9 Rx

### Wi-Fi CERTIFIED 6® (continued)

MCS 8-9 Tx MCS 10-11 Tx

Operating Mode indication

### Wi-Fi CERTIFIED™ a

#### Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU

LDPC Rx

LDPC Tx

MCS 8-9 Rx

Short Guard Interval

STBC

SU beamformer

### Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

### Wi-Fi CERTIFIED™ n

OBSS on Extension Channel





**Certification ID: WFA94244** 

Role: Access Point	
Wi-Fi CERTIFIED™ n (continued)	
Short Guard Interval STBC	
A-MPDU Tx	





**Certification ID: WFA94244** 

Role: Station	Page 5 of 7

### Wi-Fi Components

**Wi-Fi Component Operating System** 

Android

Wi-Fi Component Firmware

1.0.1.0.247.0+

### **RF Architecture**

Bands Supported	Transmit (Tx)	Receive (Rx)	
2.4 GHz	2	2	
5 GHz	2	2	

### **Certifications**

### 2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz 40 MHz Channel Width in 2.4 GHz

### **5 GHz Spectrum Capabilities**

20 MHz Channel Width in 5 GHz 40 MHz Channel Width in 5 GHz 80 MHz Channel Width in 5 GHz

### WPA2<sup>™</sup>-Enterprise 2018-04 (continued)

EAP AKA Prime
EAP SIM
EAP TLS
EAP TTLS
PEAPv0
PEAPv1

### **Protected Management Frames**

### **WMM®**

#### WMM®-Power Save

Legacy Power Save Unschedule auto PS

### WPA2™-Enterprise 2018-04

EAP methods EAP AKA

### WPA3™-Enterprise 2018-04

WPA2™-Personal 2018-04

EAP methods

EAP AKA

EAP AKA Prime

EAP SIM

EAP TLS

**EAP TTLS** 

PEAPv0

PEAPv1

### WPA3™-Personal 2019-08

### **WPA™-Enterprise**





**Certification ID: WFA94244** 

Role: Station Page 6 of 7

**WPA™-Personal** 

Wi-Fi CERTIFIED™ b

Wi-Fi Agile Multiband™

Wi-Fi CERTIFIED™ g

ANQP

BTM Query

Cellular Data capable

Wi-Fi CERTIFIED™ n

STBC

A-MPDU Tx

**OBSS** on Extension Channel

Short Guard Interval

Wi-Fi CERTIFIED 6®

BSRP Trigger frame

DL Mu PPDU multi-tone

DL MU-MIMO

HE NDP

Individual Target Wake Time

LDPC Rx

LDPC Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame

MU-RTS Trigger frame

Operating Mode indication

SU beamformee

**UL OFDMA** 

UL TB PPDU multi-tone

Wi-Fi Direct®

Wi-Fi Protected Setup™

Pushbutton

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

A-MPDU with A-MSDU

LDPC Rx

MCS 8-9 Rx

Short Guard Interval

STBC

LDPC Tx

SU beamformee





**Certification ID: WFA94244** 

Role: Source		
RF Architecture		
Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2
_		
	Bands Supported 2.4 GHz	Bands Supported Transmit (Tx)  2.4 GHz 2