Wi-Fi CERTIFIED™ Certificate

This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA109173

Product Info

Date of Certification	May 10, 2021
Company	Sky CP Ltd.
Product Name	XiOne
Product Model Variant	DE
Model Number	IP061-eb
Category	Televisions & Set Top Boxes
Sub-category	Set Top Box, Media Extender (includes players & recorders)

Summary of Certifications

CLASSIFICATION	CERTIFICATION
Access	Wi-Fi Protected Setup™
Connectivity	2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n
Optimization	WMM® Wi-Fi Agile Multiband™
Security	Protected Management Frames WPA2™-Personal 2021-01 WPA3™-Personal 2020-02
Spectrum & Regulatory Features	Spectrum & Regulatory

Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA109173

Wi-Fi Components

Wi-Fi Component Operating System

Linux, version: Linux 4.9.119

Wi-Fi Component Firmware

QCM Host SW:5.2.0.184N.009, FW: 1.1.0.0.412.0

RF Architecture

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	2	2
5 GHz	2	2

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz
40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz
40 MHz Channel Width in 5 GHz
80 MHz Channel Width in 5 GHz

Protected Management Frames

Spectrum & Regulatory

802.11h

WMM®

Max Throughput

WPA2™-Personal 2021-01

WPA3™-Personal 2020-02

Wi-Fi Agile Multiband™

ANQP
BTM Query

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU
Beamforming sounding
BSRP Trigger frame
Compressed Block Ack Rx (buffer size 256)
Compressed Block Ack Tx (buffer size 256)
DL MU-MIMO
HE NDP
Individual Target Wake Time
LDPC Rx
LDPC Tx
MCS 8-9 Rx
MCS 8-9 Tx
MCS 10-11 Rx
MCS 10-11 Tx
MU EDCA Parameter Set element
MU-BAR Trigger frame
MU-RTS Trigger frame
M-BSSID
Operating mode control field

Wi-Fi CERTIFIED 6® (continued)

Operating mode subfield in A-Control field
Operating mode indication
SU beamformee
UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

Extended 5 GHz Channel Support
RTS with BW Signaling
A-MPDU with A-MSDU
DL MU-MIMO
LDPC Rx
MCS 8-9 Rx
Short Guard Interval
STBC
LDPC Tx
SU beamformee

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

STBC
A-MPDU Tx
OBSS on Extension Channel
RIFS
Power Management
Short Guard Interval

Wi-Fi Protected Setup™

Wi-Fi Protected Setup™ (continued)

PIN
Pushbutton