

Wi-Fi CERTIFIED™ Certificate



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org/certification/programs

Certification ID: WFA109818

Product Info

| Date of Certification | January 4, 2021 |
|-----------------------|---|
| Company | NEC Corporation |
| Product Name | GX621A1 |
| Product Model Variant | GX621A1 |
| Model Number | GX621A1 |
| Category | Routers |
| Sub-category | Access Point for Home or Small Office (Wireless Router) |

Summary of Certifications

| CLASSIFICATION | CERTIFICATION |
|----------------|---|
| Connectivity | 2.4 GHz Spectrum Capabilities 5 GHz Spectrum Capabilities Wi-Fi CERTIFIED 6® Wi-Fi CERTIFIED™ a Wi-Fi CERTIFIED™ ac Wi-Fi CERTIFIED™ b Wi-Fi CERTIFIED™ g Wi-Fi CERTIFIED™ n Wi-Fi Enhanced Open™ 2020-02 |
| Optimization | WMM® WMM®-Power Save Wi-Fi Agile Multiband™ Wi-Fi EasyMesh™ |
| Security | Protected Management Frames WPA2™-Personal 2020-02 WPA3™-Personal 2020-02 WPA™-Personal |



Wi-Fi CERTIFIED[™] Certificate



Certification ID: WFA109818

| Role: Access Point | | |
|------------------------|----------------------------|--------------------------------------|
| | | |
| RF Architecture | | |
| Bands Supported | Transmit (Tx) | Receive (Rx) |
| 2.4 GHz | 2 | 2 |
| 5 GHz | 2 | 2 |
| | Bands Supported 2.4 GHz | Bands SupportedTransmit (Tx)2.4 GHz2 |

Certifications

2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz 40 MHz Channel Width in 2.4 GHz

5 GHz Spectrum Capabilities

20 MHz Channel Width in 5 GHz 40 MHz Channel Width in 5 GHz 80 MHz Channel Width in 5 GHz

Protected Management Frames

WMM®

WMM®-Power Save

WPA2[™]-Personal 2020-02

WPA3[™]-Personal 2020-02

WPA™-Personal

Wi-Fi Agile Multiband™

Wi-Fi Agile Multiband™ (continued)

Automatically populate BSS Transition candidate list Cellular Data aware

Wi-Fi CERTIFIED 6®

A-MPDU with A-MSDU Basic Trigger frame in HE MU PPDU BSRP Trigger frame Compressed Block Ack Rx (buffer size 256) Compressed Block Ack Tx (buffer size 256) DL MU-MIMO DL OFDMA Individual Target Wake Time LDPC Rx LDPC Tx MCS 8-9 Rx MCS 8-9 Tx MCS 10-11 Rx MCS 10-11 Tx MU EDCA Parameter Set element MU-BAR Trigger frame **MU-RTS** Trigger frame M-BSSID Operating Mode indication



Wi-Fi CERTIFIED[™] Certificate Certification ID: WFA109818



Role: Access Point

Page 3 of 4

Wi-Fi CERTIFIED 6® (continued)

SU beamformer SU-MIMO TXOP RTS Threshold UL OFDMA

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ ac

RTS with BW Signaling A-MPDU with A-MSDU DL MU-MIMO LDPC Rx LDPC Tx MCS 8-9 Rx Short Guard Interval STBC SU beamformer

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

OBSS on Extension Channel Short Guard Interval STBC A-MPDU Tx

Wi-Fi EasyMesh™

Backhaul Link Backhaul in 2.4 GHz

Wi-Fi EasyMesh™ (continued)

Backhaul in 5 GHz low band Backhaul over Ethernet Fronthaul Access Point Fronthaul in 2.4 GHz Fronthaul in 5 GHz low band Fronthaul in 5 GHz high band Unassociated STA Link Metrics Reporting Backhaul onboarding with Pushbutton

Wi-Fi Enhanced Open[™] 2020-02



Wi-Fi CERTIFIED™ Certificate

Certification ID: WFA109818



Page 4 of 4

Role: Controller

Wi-Fi Components

Wi-Fi Component Operating System

Linux

Certifications

Wi-Fi EasyMesh™