

## Wi-Fi CERTIFIED® Certificate



This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing. Learn more: www.wi-fi.org

## **Certification ID: WFA109988**

## **Product Info**

Date of Certification January 14, 2021

Company Linksys USA, Inc

Product Name Linksys Tri-Band Wi-Fi 6E Router

Product Model Variant MX85EC, MX85WH, MX85MS

Model Number MX8500

**Category** Routers

**Sub-category** Access Point for Home or Small Office (Wireless Router)

## **Summary of Certifications**

CLASSIFICATION CERTIFICATION

Access Wi-Fi Protected Setup™

Network management WMM®

WMM®-Power Save Wi-Fi Agile Multiband™

**Security** Protected Management Frames

WPA2<sup>™</sup>-Personal 2020-02 WPA3<sup>™</sup>-Personal 2020-02

Wi-Fi Enhanced Open™ 2020-02

Wi-Fi (MAC/PHY) 2.4 GHz Spectrum Capabilities

5 GHz Spectrum Capabilities6 GHz Spectrum Capabilities

Wi-Fi CERTIFIED 6®
Wi-Fi CERTIFIED™ a
Wi-Fi CERTIFIED™ b
Wi-Fi CERTIFIED™ g
Wi-Fi CERTIFIED™ n



# Wi-Fi CERTIFIED® Certificate

**Certification ID: WFA109988** 



## Role: Access Point Page 2 of 3

#### Wi-Fi Components

## Wi-Fi Component Operating System

Linux

## Wi-Fi Component Firmware

2.4-01801

#### **RF Architecture**

Bands Supported	Transmit (Tx)	Receive (Rx)
2.4 GHz	4	4
5 GHz	4	4
6 GHz	4	4

#### Certifications

#### 2.4 GHz Spectrum Capabilities

20 MHz Channel Width in 2.4 GHz 40 MHz Channel Width in 2.4 GHz

#### **5 GHz Spectrum Capabilities**

20 MHz Channel Width in 5 GHz 40 MHz Channel Width in 5 GHz 80 MHz Channel Width in 5 GHz

#### **6 GHz Spectrum Capabilities**

20 MHz Channel Width in 6 GHz 40 MHz Channel Width in 6 GHz 80 MHz Channel Width in 6 GHz 160 MHz Channel Width in 6 GHz

#### **Protected Management Frames**

**WMM®** 

**WMM®-Power Save** 

## WPA2™-Personal 2020-02

#### WPA3™-Personal 2020-02

#### Wi-Fi Agile Multiband™

#### Wi-Fi CERTIFIED 6®

4 antenna support

A-MPDU with A-MSDU

Basic Trigger frame in HE MU PPDU

**BSRP** Trigger frame

Compressed Block Ack Rx (buffer size 256)

Compressed Block Ack Tx (buffer size 256)

DL MU-MIMO

DL OFDMA

Individual Target Wake Time

LDPC Rx

LDPC Tx

MCS 8-9 Rx

MCS 8-9 Tx

MCS 10-11 Rx

MCS 10-11 Tx

MU EDCA Parameter Set element

MU-BAR Trigger frame



# Wi-Fi CERTIFIED® Certificate

**Certification ID: WFA109988** 



Role: Access Point Page 3 of 3

## Wi-Fi CERTIFIED 6® (continued)

MU-RTS Trigger frame

Operating mode subfield in A-Control field

Operating mode indication

Operating mode UL MU Rx

SU beamformer

TXOP RTS Threshold

**UL OFDMA** 

Wi-Fi 6E

#### Wi-Fi CERTIFIED™ a

#### Wi-Fi CERTIFIED™ ac

RTS with BW Signaling

A-MPDU with A-MSDU

DL MU-MIMO

LDPC Rx

LDPC Tx

MCS 8-9 Rx

**Short Guard Interval** 

STBC

SU beamformer

#### Wi-Fi CERTIFIED™ b

#### Wi-Fi CERTIFIED™ g

#### Wi-Fi CERTIFIED™ n

**OBSS** on Extension Channel

Short Guard Interval

STBC

A-MPDU Tx

Wi-Fi Enhanced Open™ 2020-02

### Wi-Fi Protected Setup™

PIN

Pushbutton